



# PRIME PX ATX 3



## SPECIAL FEATURES

- ❖ ATX 3.1 and PCIe 5.1 Compatible
- ❖ Super-High Efficiency, 80 PLUS® Platinum Certified
- ❖ Cybenetics ETA Titanium and Lambda A Certified
- ❖ Fully Modular
- ❖ Top-Quality 135 mm Fluid Dynamic Bearing Fan
- ❖ Digital Hybrid Fan Control
- ❖ Micro Tolerance Load Regulation (MTLR) [0.5 %]
- ❖ Super Low Ripple Noise [under 20 mV]
- ❖ Cable-free Connection Design
- ❖ Gold Plated High Current Terminal (MB, CPU and PCIe)
- ❖ Multi-GPU Technology Support

## POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
PRIME PX-1600	25 A	25 A	133.3 A	0.5 A	3 A	1600 W
		125 W	1600 W	6 W	15 W	



## CONNECTOR QUANTITY

Cable								
Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 700 mm	12V-2x6 (12+4 Pins) 700 mm	PCI-E (8P / 6P) 750 mm	SATA 950 mm	SATA 3.3 550 mm	Peripheral (4P) 690 mm	
PRIME PX-1600	1	3	2	6	16	2	3	



For more information on Cybenetics certifications please visit: [www.cybenetics.com](http://www.cybenetics.com).



Compliance:

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 210 mm (L) x 150 mm (W) x 86 mm (H)

Specifications may change without prior notice



Headquarters [sales@seasonic.com](mailto:sales@seasonic.com)  
 USA [ssa.sales@seasonic.com](mailto:ssa.sales@seasonic.com)  
 Europe [sse.sales@seasonic.com](mailto:sse.sales@seasonic.com)