Huawei CloudEngine S6730-H-V2 Series PEN Central Switches Datasheet

Huawei CloudEngine S6730-H-V2 series PEN central switches are next-generation Passive Enternet Optical PEN(Passive Ethernet Network) central switches that provide 96 x 2.5/10GE downlink optical ports, 4 x 25GE and 2 x 100GE uplink optical ports, and provide one extended slot.

Introduction

Huawei CloudEngine S6730-H-V2 series PEN central switches are next-generation Passive Enternet Optical PEN(Passive Ethernet Network) central switches that offer high performance, high reliability, cloud management, and intelligent operations and maintenance (O&M). They are purpose-built with security, IoT, and cloud in mind. With these traits, CloudEngine S6730-H-V2 can be widely used in enterprise campuses, colleges/universities, and other scenarios.

CloudEngine S6730-H-V2 switches offer 2.5GE, 10GE, 25GE, and 100GE port types, flexibly adapting to diversified network bandwidth requirements. They also support cloud management and implement cloud-managed network services throughout the full lifecycle from planning, deployment, monitoring, experience visibility, and fault rectification, all the way to network optimization, greatly simplifying network management.


CloudEngine S6730-H-V2 support free mobility, enables consistent user experience no matter the user location or IP address, fully meeting enterprises' demands for mobile offices.


CloudEngine S6730-H-V2 switches support VXLAN to implement network virtualization, achieving multi-purpose networks and multi-network convergence for greatly improved network capacity and utilization. As such, CloudEngine S6730-H-V2 switches are an ideal choice for building next-generation IoT converged networks in terms of cost, flexibility, and scalability.

Product Overview

Models and Appearances

The following models are available in CloudEngine S6730-H-V2 series optical switches.


Appearance	Description
 CloudEngine S6730-H6FX4Y2CZ-V2	• 6 x CFP2 PEN central ports, 4 x 25GE SFP28, 2 x 100GE QSFP28 ports One extended slot • Dual pluggable power modules, 1+1 power backup • Switching capacity: 2.92Tbps/4.8Tbps* *Note: A single CFP2 port supports 16 x 2.5/10GE SFP+ channels, supporting 96 access devices in total*
 HW-PEN-16LC-2KM	• PEN passive aggregation module, two channels of 2:8 passive optical splitting, uplink backup, mixed use of optical modules in a group, 2 km transmission distance (for campus products)

Appearance	Description
 HW-PEN-16LC-10KM	• PEN passive aggregation module, two channels of 2:8 passive optical splitting, uplink backup, no mixed use of optical modules in a group, 10 km transmission distance (for campus products)(for campus porducts)
 HW-PEN-BOX-03	• PEN passive aggregation module subrack, three slots, rack-mounted (for campus porducts)
 CFP2-160G-LR-CORE	• CFP2-16*10G/2.5G-PEN Central Optical Module (10km, LC)
 SFP+-10G-LR	• SFP+-10G-LR-A1 • SFP+-10G-LR-A2 • SFP+-10G-LR-A3 • SFP+-10G-LR-A4 • SFP+-10G-LR-A5 • SFP+-10G-LR-A6 • SFP+-10G-LR-A7 • SFP+-10G-LR-A8 • 8 optical modules support any mixed insertion in 1 group

Subcards

The following table lists the subcards applicable to the CloudEngine S6730-H-V2.

Technical specifications of the subcards applicable to the CloudEngine S6730-H-V2 series

Subcards	Technical Specifications	Applied Switch Model
 HSIC-X08S000	• 8*10GE SFP+ or 4*25GE SFP28 (only ports 1 to 4 support 25GE) • Dimensions without packaging (H x W x D) [mm(in.)]: 39.1 mm x 100.1 mm x 220 mm (1.54 in. x 3.94 in. x 8.66 in.) • Weight without packaging [kg(lb)]: 0.44 kg (0.97 lb) • Maximum power consumption [W]: 38.5 W • Maximum heat dissipation [BTU/hour]: 131.37 BTU/hour	CloudEngine S6730-H6FX4Y2CZ-V2
 HSIC-Y08S000	• 8*25GE SFP28 • Dimensions without packaging (H x W x D) [mm(in.)]: 39.1 mm x 100.1 mm x 220 mm (1.54 in. x 3.94 in. x 8.66 in.) • Weight without packaging [kg(lb)]: 0.44 kg (0.97 lb) • Maximum power consumption [W]: 38.5 W • Maximum heat dissipation [BTU/hour]: 131.37 BTU/hour	CloudEngine S6730-H6FX4Y2CZ-V2
 HSIC-Q04S000	• 4*40GE QSFP ports or 2*100GE QSFP28 ports (only ports 1/3 support 100GE） • Dimensions without packaging (H x W x D) [mm(in.)]: 39.1 mm x 100.1 mm x 220 mm (1.54 in.	CloudEngine S6730-H6FX4Y2CZ-V2

Subcards	Technical Specifications	Applied Switch Model
	x 3.94 in. x 8.66 in.) • Weight without packaging [kg(lb)]: 0.44 kg (0.97 lb) • Maximum power consumption [W]: 40 W • Maximum heat dissipation [BTU/hour]: 136.48 BTU/hour	
 HSIC-C04S000	• 4*100GE QSFP28 ports • Dimensions without packaging (H x W x D) [mm(in.)]: 39.1 mm x 100.1 mm x 220 mm (1.54 in. x 3.94 in. x 8.66 in.) • Weight without packaging [kg(lb)]: 0.44 kg (0.97 lb) • Maximum power consumption [W]: 48 W • Maximum heat dissipation [BTU/hour]: 163.78 BTU/hour	CloudEngine S6730-H6FX4Y2CZ-V2

Fan Module

The following table lists the fan module on CloudEngine S6730-H-V2 series optical switches.

Fan Module	Technical Specifications	Applied Switch Model
 FAN-031A-B	• Dimensions (W x D x H): 40 mm x 100.3 mm x 40 mm • Number of fans: 1 • Weight: 0.1 kg • Maximum power consumption: 21.6 W • Maximum fan speed: 24500±10% revolutions per minute (RPM) • Maximum wind rate: 31 cubic feet per minute (CFM) • Hot swap: Supported	• CloudEngine S6730-H6FX4Y2CZ-V2

Power Supply

The following table lists the power supplies on CloudEngine S6730-H-V2 optical series.

Power Module	Technical Specifications	Applied Switch Model
 PDC400S12-CB	• Dimensions (H x W x D): 39.6 mm x 66.0 mm x 215 mm (1.56 in. x 2.6 in. x 8.46 in.) • Weight without packaging [kg(lb)]: 0.679 kg (1.5 lb) • Rated input voltage range: – +48 V DC – -48 V DC to -60 V DC • Maximum input voltage range: – +40 V DC to +57 V DC – -38.4 V DC to -72 V DC • Maximum input current: 12 A • Maximum output current: 35.52 A • Maximum output power: 400 W • Hot swapping: Supported	• CloudEngine S6730-H6FX4Y2CZ-V2

Power Module	Technical Specifications	Applied Switch Model
 PAC600S12-PB	• Dimensions (H x W x D): 39.6 mm x 66.0 mm x 215 mm (1.56 in. x 2.6 in. x 8.46 in.) • Weight without packaging [kg(lb)]: 1 kg (2.2 lb) • Rated input voltage range: – AC input: 100 V to 240 V, 50 Hz/60 Hz – High-voltage DC input: 240 V DC • Maximum input voltage range: – AC input: 90 V to 290 V, 45 Hz to 65 Hz – High-voltage DC input: 190 V DC to 290 V DC • Maximum input current: – 100 V AC to 240 V AC: 8 A – 240 V DC: 4 A • Maximum output current: 50 A • Rated output voltage: 12 V • Maximum output power: 600 W • Hot swapping: Supported	• CloudEngine S6730-H6FX4Y2CZ-V2
 PAC1K2S12-PB	• Dimensions (H x W x D): 39.6 mm x 66 mm x 215 mm • Weight without packaging [kg(lb)]: 0.844 kg (1.86 lb) • Rated input voltage range: – 200V AC～240V AC；50/60Hz – 100V AC～130V AC；50/60Hz – 240V DC • Maximum input voltage range: – AC：90V AC～290V AC；45Hz～65Hz – HVDC：190V DC～290V DC • Maximum input current: – 100V AC～130V AC：10A – 200V AC～240V AC：8A – 240V DC：8A • Maximum output current: 100 A • Maximum output power: 1200 W • Hot swapping: Supported	• CloudEngine S6730-H6FX4Y2CZ-V2
 PDC1K2S12-CE	• Dimensions (H x W x D): 40 mm x 66 mm x 215 mm (1.6 in. x 2.6 in. x 8.5 in.) • Weight without packaging [kg(lb)]: 1.0 kg (2.2 lb) • Rated input voltage range: – +48 V DC – -48 V DC to -60 V DC • Maximum input voltage range: – +40 V DC to +57 V DC – -38.4 V DC to -72 V DC • Maximum input current: 38 A • Maximum output current: 100 A	• CloudEngine S6730-H6FX4Y2CZ-V2


Power Module	Technical Specifications	Applied Switch Model
	• Maximum output power: 1200 W • Hot swapping: Supported	

The S6730-H-V2 uses pluggable power modules. It can be configured with a single power module or double power modules for 1+1 power redundancy.

Product Features and Highlights

High-quality Ethernet Solution

- High-quality Ethernet solution: ultra-high-density central switch + passive aggregation module, implementing exclusive bandwidth and passive weak-current communication.



- 2.5/10GE all-optical indoor access, meeting high-density access requirements:

  Ultra-high density: 1U core switch supports access of 96 AP/RUs. One core switch and two passive aggregation modules are required. Only 12 optical fibers (between corridors) are required. 96 APs can be connected.

  High rate: 2.5/10GE all-optical indoor access. Works with remote modules and Wi-Fi 6/7 APs to meet high-density wired and wireless access requirements and provide ultra-fast upstream rates.

Enable Networks to be More Agile for Services

- Built-in high-speed and flexible processor chips, with their flexible packet processing and traffic control capabilities, CloudEngine S6730-H-V2 series switches are close to services, meeting current and future challenges, and helping customers build scalable networks.
- CloudEngine S6730-H-V2 series switches support fully customizing the forwarding mode, forwarding behavior, and search algorithm of traffic. New services are implemented through microcode programming. Customers do not need to replace new hardware and new services can be rolled out within six months.
- CloudEngine S6730-H-V2 series switches provide open interfaces and user-defined forwarding processes to meet customized service requirements of enterprises. Enterprises can use multi-layer open interfaces to develop new protocols and functions independently. They can also hand over their requirements to vendors and jointly develop them to build an enterprise-dedicated campus network.

Delivering Abundant Services More Agilely

- Huawei switches support post-quantum cryptography (PQC) algorithms and encryption capabilities within transport security protocols, effectively defending against decryption threats posed by quantum computing to deliver future-proof quantum-resistant security for network infrastructure.

- With the unified user management function, the CloudEngine S6730-H-V2 series switches authenticates both wired and wireless users, ensuring a consistent user experience no matter whether they are connected to the network through wired or wireless access devices. The unified user management function supports various authentication methods, including 802.1x, MAC address, and is capable of managing users based on user groups, domains, and time ranges. These functions visualize user and service management and boost the transformation from device-centric management to user experience-centric management.
- The CloudEngine S6730-H-V2 series switches provide excellent quality of service(QoS) capabilities and supports queue scheduling and congestion control algorithms. Additionally, it adopts innovative priority queuing and multi-level scheduling mechanisms to implement fine-grained scheduling of data flows, meeting service quality requirements of different user terminals and services.

Fine-Grained Network Management and Visualized Fault Diagnosis

- In-situ Flow Information Telemetry (IFIT) is an in-band Operations, Administration, and Maintenance (OAM) measurement technology that uses service packets to measure real performance indicators of an IP network, such as the packet loss rate and delay. IFIT can significantly improve the timeliness and effectiveness of network O&M, thereby promoting the development of intelligent O&M.
- Three IFIT modes are available: application-level quality measurement, tunnel-level quality measurement, and native-IP IFIT measurement. Currently, CloudEngine S6730-H-V2 series switches support native-IP IFIT measurement only. By providing in-band measurement capabilities, CloudEngine S6730-H-V2 series switches can monitor indicators such as the delay and packet loss rate of service flows in real time. CloudEngine S6730-H-V2 series switches also offer visualized O&M capabilities to centrally manage and control networks and graphically display performance data. Designed with IFIT capabilities featuring high measurement precision and easy deployment, CloudEngine S6730-H-V2 series switches are ideal for constructing an intelligent O&M system and stand out with future-proof scalability.

Flexible Ethernet Networking

- In addition to traditional Spanning Tree Protocol (STP), Rapid Spanning Tree Protocol (RSTP), and Multiple Spanning Tree Protocol (MSTP), the CloudEngine S6730-H-V2 series switches support Huawei-developed Smart Ethernet Protection (SEP) technology and the latest Ethernet Ring Protection Switching (ERPS) standard. SEP is a ring protection protocol specific to the Ethernet link layer, and applies to various ring network topologies, such as open ring topology, closed ring topology, and cascading ring topology. This protocol is reliable, easy to maintain, and implements fast service switching within 50 ms. ERPS is defined in ITU-T G.8032. It implements millisecond-level protection switching based on traditional Ethernet MAC and bridging functions.
- CloudEngine S6730-H-V2 series switches support Smart Link and Virtual Router Redundancy Protocol (VRRP), which implement backup of uplinks. One CloudEngine S6730-H-V2 series switch can connect to multiple core switches through multiple links, significantly improving reliability of aggregation devices.

Mature IPv6 Features

- The CloudEngine S6730-H-V2 series swithes are developed based on the mature, stable VRP and supports IPv4/IPv6 dual stacks, IPv6 routing protocols (RIPng, OSPFv3, BGP4+, and IS-IS for IPv6). With these IPv6 features, the CloudEngine S6730-H-V2 can be deployed on a pure IPv4 network, a pure IPv6 network, or a shared IPv4/IPv6 network, helping achieve IPv4-to-IPv6 transition.

Intelligent Stack (iStack)

- CloudEngine S6730-H-V2 series switches support the iStack function that combines multiple switches into a logical switch. Member switches in a stack implement redundancy backup to improve device reliability and use inter-device link aggregation to improve link reliability. iStack provides high network scalability. You can increase a stack's ports, bandwidth, and processing capability by simply adding member switches. iStack also simplifies device configuration and management. After a stack is set up, up to nine physical switches can be virtualized into one logical device. You can log in to any member switch in the stack to manage all the member switches in it.

Cloud-based Management

- The Huawei cloud management platform allows users to configure, monitor, and inspect switches on the cloud, reducing on-site deployment and O&M manpower costs and decreasing network OPEX.

VXLAN Features

- VXLAN is used to construct a Unified Virtual Fabric (UVF). As such, multiple service networks or tenant networks can be deployed on the same physical network, and service and tenant networks are isolated from each other. This capability truly achieves 'one network for multiple purposes'. The resulting benefits include enabling data transmission of different services or customers, reducing the network construction costs, and improving network resource utilization.
- This series switches are VXLAN-capable and allow centralized and distributed VXLAN gateway deployment modes. These switches also support the BGP EVPN protocol for dynamically establishing VXLAN tunnels and can be configured using NETCONF/YANG.

Open Programmability System(OPS)

- Open Programmability System (OPS) is an open programmable system based on the Python language. IT administrators can program the O&M functions of a switch through Python scripts to quickly innovate functions and implement intelligent O&M.

Intelligent O&M

- This series switches provides telemetry technology to collect device data in real time and send the data to Huawei campus network analyzer(iMaster NCE-CampusInsight). The CampusInsight analyzes network data based on the intelligent fault identification algorithm, accurately displays the real-time network status, effectively demarcates and locates faults in a timely manner, and identifies network problems that affect user experience, accurately guaranteeing user experience.
- The CloudEngine S6730-H-V2 supports the WebMaster solution, featuring an embedded local management system. It automatically discovers network topology and provides full-network visibility, including topology views, network elements (NEs), and device alarms. The solution also enables unified management of switches, AR routers, and APs—without requiring an external network management system.WebMaster offers a graphical interface for intuitive operations, including guided service provisioning, one-click batch upgrades, zero-configuration device replacement, and automatic authentication and onboarding of NEs. It can also detect loops caused by incorrect cable connections and eliminate them automatically.With its rich feature set, WebMaster enables the entire campus network to be visible, manageable, and controllable—all through a single device.

Intelligent Upgrade

- Switches support the intelligent upgrade feature. Specifically, switches obtain the version upgrade path and download the newest version for upgrade from the Huawei Online Upgrade Platform (HOUP). The entire upgrade process is highly automated and achieves one-click upgrade. In addition, preloading the version is supported, which greatly shortens the upgrade time and service interruption time.
- The intelligent upgrade feature greatly simplifies device upgrade operations and makes it possible for the customer to upgrade the version independently. This greatly reduces the customer's maintenance costs. In addition, the upgrade policies on the HOUP platform standardize the upgrade operations, which greatly reduces the risk of upgrade failures.

Product Specifications

The following table describes the functions and features available on the CloudEngine S6730-H-V2 series switches.

Functions and Features

Category	Service Features
User management	Unified user management
	802.1X authentication
	MAC authentication
	Traffic- and duration-based accounting
	User authorization based on user groups, domains, and time ranges
MAC	Automatic MAC address learning and aging
	384K MAC entries (MAX)

Category	Service Features
	Static, dynamic, and blackhole MAC address entries
	Source MAC address filtering
	MAC address learning limiting based on ports and VLANs
VLAN	4K VLANs
	Access mode, Trunk mode and Hybrid mode
	Default VLAN
	QinQ and enhanced selective QinQ
	VLAN Stacking
	Dynamic VLAN assignment based on MAC addresses
ARP	ARP Snooping
DHCP	DHCPv4 Client, DHCPv4 Relay, DHCPv4 Server, DHCPv4 Snooping
	DHCPv6 Client, DHCPv6 Relay, DHCPv6 Server, DHCPv6 Snooping
IP routing	IPv4 dynamic routing protocols such as RIP, OSPF, IS-IS, and BGP
	IPv6 dynamic routing protocols such as RIPng, OSPFv3, ISISv6, and BGP4+
	Routing Policy, Policy-Based Routing
	VRF
	Up to 256K FIBv4 entries (MAX)
	Up to 80K FIBv6 entries (MAX)
Segment Routing	SRv6 BE (L3 EVPN)
	BGP EVPN
	SRv6 configuration through NETCONF
Multicast	IGMPv1/v2/v3 and IGMP v1/v2/v3 Snooping
	PIM-DM, PIM-SM, and PIM-SSM
	Fast-leave mechanism
	Multicast VPN
	IP multicast over VXLAN, including Layer 2/Layer 3 multicast over VXLAN
	Multicast traffic control
	Multicast querier
	Multicast protocol packet suppression
MPLS	MPLS-LDP
	MPLS-L3VPN
	MPLS Qos
	MPLS TE
VPN	MPLS BGP VPN, VPWS, VPLS, GRE

Category	Service Features
VXLAN	Centralized gateway
	Distributed gateway
	BGP-EVPN
	Configures VXLANs through NETCONF
QoS	Traffic classification based on Layer 2 headers, Layer 3 protocols, Layer 4 protocols, and 802.1p priority
	Actions such as ACL, Committed Access Rate (CAR), re-marking, and scheduling
	Queuing algorithms, such as PQ, DRR, WDRR, and PQ+DRR, PQ+WDRR
	Congestion avoidance mechanisms such as WRED and tail drop
	Traffic shaping
	Eight queues on each interface
	Network Slicing
Native-IP IFIT(iPCA 2.0)	Marks the real service packets to obtain real-time count of dropped packets and packet loss ratio
	The statistical period can be modified
	Two-way frame delay measurement
Ethernet loop protection	STP (IEEE 802.1d), RSTP (IEEE 802.1w), and MSTP (IEEE 802.1s).
	BPDU protection, root protection, and loop protection
	G.8032 Ethernet Ring Protection Switching (ERPS)
Reliability	M-LAG
	Service interface-based stacking
	Maximum number of stacked devices: 9
	Stack bandwidth (Bidirectional)
	Link Aggregation Control Protocol (LACP) and E-Trunk
	Virtual Router Redundancy Protocol (VRRP) and Bidirectional Forwarding Detection (BFD) for VRRP
	BFD for BGP/IS-IS/OSPF/static routes
	Eth-OAM 802.1ag(CFM)
	Smartlink
	LLDP
System management	Console terminal service
	Telnet/IPv6 Telnet terminal service
	SSH v1.5
	SSH v2.0
	SNMP v1/v2c/v3
	FTP, TFTP, SFTP

Category	Service Features
	sFlow
	BootROM upgrade and remote in-service upgrade
	Hot patch
	User operation logs
	Open Programmability System (OPS)
	Streaming Telemetry
	WebMaster Management
Security and management	NAC
	Port security
	RADIUS and HWTACACS authentication for login users
	Command line authority control based on user levels, preventing unauthorized users from using command configurations
	Defense against DoS attacks, Transmission Control Protocol (TCP) SYN Flood attacks, User Datagram Protocol (UDP) Flood attacks, broadcast storms, and heavy traffic attacks
	IPv6 RA Guard
	CPU hardware queues to implement hierarchical scheduling and protection for protocol packets on the control plane
	Remote Network Monitoring (RMON)
	Secure boot
	Netstream
	Port mirroring
Wireless management (integrated WLAN AC): Basic WLAN services	Hot backup for devices with integrated WLAN AC functionality in cluster mode
	2.4G & 5G load balancing
	5G-prior access
Wireless management (integrated WLAN AC): AP management	Total number of managed APs: 1K
	An IPv4 network between an AP and a WLAN AC
	AP blacklist
	AP whitelist
	Sets the AP access control mode
	AP configuration and management
	AP LLDP topology awareness
Wireless management (integrated WLAN AC): Wireless user management	User roaming within a WLAN AC
	AP-based user location
	802.1X authentication
	MAC address authentication
	Portal authentication

Category	Service Features
Wireless management (integrated WLAN AC): CAPWAP	Direct data forwarding on L2/L3 networks
	Tunnel-based data forwarding on L2/L3 networks
	CAPWAP tunnel encryption
Wireless management (integrated WLAN AC): RF management	802.11a/b/g/n
	802.11ac wave1/wave2
	802.11ax
	802.11be
	Sets RF interference monitoring and avoidance
	Detects co-channel interference, adjacent interference, and interference from other devices and STAs
	Automatically selects channels and power when APs go online
	Dynamic power and channel optimization
Wireless management (integrated WLAN AC): WLAN QoS	Rate limiting of upstream and downstream traffic on the air interface based on the VAP
	Rate limiting of upstream and downstream traffic on the air interface based on users
	CAR for WLAN users

Hardware Specifications

The following table lists hardware specifications of the CloudEngine S6730-H-V2 series optical switches.

Item		CloudEngine S6730-H6FX4Y2CZ-V2
Physical specifications	Chassis dimensions (H x W x D, mm)	43.6 mm x 442.0 mm x 420.0 mm (1.72 in. x 17.4 in. x 16.54 in.)
	Chassis height	1U
	Weight with packaging [kg (lb)]	9.38 kg (20.68 lb)
Extended slot	HSIC-X08S000	One extended slot, 8*10GE SFP+ ports or 4*25GE SFP28 ports (only ports 1 to 4 support 25GE)
	HSIC-Y08S000	One extended slot, 8*25GE SFP28
	HSIC-Q04S000	4*40GE QSFP ports or 2*100GE QSFP28 ports (only ports 1/3 support 100GE）
	HSIC-C04S000	4*100GE QSFP28
Fixed port	CFP8 super-aggregation ports	6
	25GE port	4
	100GE port	2
Management port	ETH management port	Supported
	Console port (RJ45)	Supported
	USB port	USB 2.0
CPU	Frequency	1.4 GHz

Item		CloudEngine S6730-H6FX4Y2CZ-V2
	Cores	4
Memory	Memory (RAM)	4GB
	Flash	Hardware: 4 GB
Power supply system	Power supply type	• 400 W DC (pluggable) • 600 W AC (pluggable) • 1200 W AC (pluggable) • 1200 W DC (pluggable)
	Rated voltage range	• AC input: 100 V AC to 240 V AC; 50/60 Hz • High-voltage DC input: 240 V DC • DC input: –48 V DC to –60 V DC
	Maximum voltage range	• AC input: 90 V AC to 290 V AC; 45–65 Hz • High-voltage DC input: 190 V DC to 290 V DC • DC input: -38.4 V DC to -72 V DC
	Maximum input current	The current specifications are related to the pluggable power module. For details, see Pluggable Power Modules.
	Typical power consumption (30% of traffic load, tested according to ATIS standard)	234 W
	Maximum power consumption (100% throughput, full speed of fans)	281W
Heat dissipation system	Heat dissipation mode	Air cooling for heat dissipation, intelligent fan speed adjustment
	Number of fan modules	3, Fan modules are pluggable
	Airflow	Air intake from front and right and air exhaust from rear
Environment parameters	Long-term operating temperature	• 0-1800 m: -5°C to 45°C • 1800-5000 m: The operating temperature decreases 1°C for every 220 m increase in altitude.
	Storage temperature	-40°C to +70°C
	Relative humidity	5% RH to 95% RH, non-condensing
	Operating altitude	0-5000 m
	Noise at normal temperature (acoustic power) [dB(A)]	53.5 dB(A)
	Noise at normal temperature (acoustic pressure) [dB(A)]	50.5 dB(A)
	Surge protection specification (power port)	• Using AC power modules: ±6 kV in differential mode, ±6 kV in common mode • Using DC power modules: ±2 kV in differential mode, ±4 kV in common mode
Reliability	MTBF (year)	51.81
	Availability	> 0.99999
Certification		• EMC certification

Item	CloudEngine S6730-H6FX4Y2CZ-V2
	• Safety certification • Manufacturing certification **NOTE** For details about certifications, see the section Safety and Regulatory Compliance.

Performance Specification

Entries	S6730-H-V2 series switches
Number of dynamic MAC address entries	Up to 384K
Number of static MAC address entries	1024
Maximum number of VLANs	4094
Number of VLANIF interfaces	4094
IPv4 routing entries	Up to 256000
IPv6 routing entries	Up to 80000
Number of ARP entries	Up to 140000
Number of ND entries	Up to 80000
ACL scale entries	6.5K@320 bits (K = 1024)
IPv4/IPv6 multicast L2 entries	64K/4K
IPv4/IPv6 multicast L3 entries	64K/4K
Device buffer (byte)	18MB
Jumbo frames	9600

Licensing

Licensing

This series switches supports both the traditional feature-based licensing mode and the latest Huawei IDN One Software (N1 mode for short) licensing mode. The N1 mode is ideal for deploying Huawei CloudCampus Solution in the on-premises scenario, as it greatly enhances the customer experiences in purchasing and upgrading software services with simplicity.

Software Package Features in N1 Mode


Switch Functions	N1 Basic Software	N1 Foundation Software Package	N1 Advanced Software Package
Basic network functions: Layer 2 functions, IPv4, IPv6, and others Note: For details, see the Service Features	√	√	√
Basic network automation based on the iMaster NCE-Campus: • Basic automation: Plug-and-play, SSID • Basic monitoring: Application visualization • NE management: Image and topology management	×	√	√

Switch Functions	N1 Basic Software	N1 Foundation Software Package	N1 Advanced Software Package
and discovery • User access authentication			
Automation and intelligent O&M: Basic functions for intelligent network analysis of CampusInsight.	×	√	√
Advanced network automation and intelligent O&M: VXLAN, free mobility, Endpoint plug&play of iMaster NCE-Campus and Application analysis function of CampusInsight.	×	×	√

Networking and Applications

Large-scale Enterprise Campus Network

CloudEngine S6730-H-V2 series optical switches can be deployed at the aggregation layer of a large-scale enterprise campus network, creating a highly reliable, scalable, and manageable enterprise campus network.



Product Accessories

Optical Modules and Fibers

CFP8 super-aggregation ports support optical modules and cables

- CFP8 optical module

25GE SFP28 ports support optical modules and cables

- GE eSFP optical module

- GE SFP optical module
- GE-CWDM optical module
- GE-DWDM optical module
- 10GE SFP+ optical module
- 10GE-CWDM optical module
- 10GE-DWDM optical module
- 25GE SFP28 optical module
- 1 m, 3 m, 5 m, and 10 m SFP+ high-speed cables
- 3 m and 10 m SFP+ AOC cables
- 1 m, 3 m, 5 m SFP28 high-speed cables
- 3 m, 5 m, 7 m, and 10 m SFP28 AOC cables

40GE/100GE QSFP28 ports support optical modules and cables

- QSFP+ optical module
- QSFP28 optical module
- 1 m, 3 m, and 5 m QSFP+ to QSFP+ high-speed copper cables
- 10 m QSFP+ to QSFP+ AOC cable
- 1 m QSFP28 to QSFP28 high-speed copper cable
- 10 m QSFP28 to QSFP28 AOC cable

Stack Cables

CloudEngine S6730-H-V2 series optical switches support service port stacking. The applicable stack cables are as follows:

Ports Supporting Stack Cable Connections	Pluggable Modules and Cables for Ports	Rate of a Single Port in a Stack
25GE	• All SFP+ optical modules supported by the device and the matching optical fibers • 1 m, 3 m, 5 m, and 10 m SFP+ high-speed cables • 3 m and 10 m SFP+ AOC cables • 0.5 m and 1.5 m SFP+ dedicated stack cables (configuration required) (Note: The preceding cables can be used only after the port rate decreases.)	10 Gbit/s
	• All SFP28 optical modules supported by the device and the matching optical fibers • 1 m SFP28 high-speed cable • 3 m, 5 m, 7 m, and 10 m SFP28 AOC cables	25 Gbit/s
40GE	• All QSFP+ optical modules supported by the device and the matching optical fibers • 1 m, 3 m, and 5 m QSFP+ to QSFP+ high-speed cables • 10 m QSFP+ to QSFP+ AOC cable	40 Gbit/s
100GE	• All QSFP+ optical modules supported by the device and the matching optical fibers • 1 m, 3 m, and 5 m QSFP+ to QSFP+ high-speed cables • 10 m QSFP+ to QSFP+ AOC cable (Note: The preceding cables can be used only after the port rate decreases.)	40 Gbit/s

Ports Supporting Stack Cable Connections	Pluggable Modules and Cables for Ports	Rate of a Single Port in a Stack
	• All QSFP28 optical modules supported by the device and the matching optical fibers • 1 m and 3 m QSFP28 to QSFP28 high-speed cables • 10 m QSFP28 to QSFP28 AOC cable • 2 m dedicated stack cable (configuration-free)	100 Gbit/s

Safety and Regulatory Compliance

The following table lists the safety and regulatory compliance of the CloudEngine S6730-H-V2 series optical switches.

Certification Category	Description
Safety	IEC 62368-1
	EN 62368-1
	UL 62368-1
	CSA C22.2 No 62368-1
Electromagnetic Compatibility (EMC)	CISPR32
	CISPR35
	EN 55032
	EN 55035
	ETSI EN 300 386
	CFR 47 FCC Part 15
	ICES 003
	AS/NZS CISPR32
	VCCI
	IEC61000-4-2
Environment	RoHS
	REACH
	WEEE
Laser safety	IEC60825-1
	IEC60825-2
	EN60825-1
	EN60825-2

NOTE

- EMC: electromagnetic compatibility
- CISPR: International Special Committee on Radio Interference
- EN: European Standard

- ETSI: European Telecommunications Standards Institute
- CFR: Code of Federal Regulations
- FCC: Federal Communication Commission
- IEC: International Electrotechnical Commission
- AS/NZS: Australian/New Zealand Standard
- VCCI: Voluntary Control Council for Interference
- UL: Underwriters Laboratories
- CSA: Canadian Standards Association
- IEEE: Institute of Electrical and Electronics Engineers

MIB and Standards Compliance

Supported MIBs

Category	MIB
Public MIB	• BRIDGE-MIB • DISMAN-NSLOOKUP-MIB • DISMAN-PING-MIB • DISMAN-TRACEROUTE-MIB • ENTITY-MIB • EtherLike-MIB • IF-MIB • IP-FORWARD-MIB • IPv6-MIB • LAG-MIB • LLDP-EXT-DOT1-MIB • LLDP-EXT-DOT3-MIB • LLDP-MIB • NOTIFICATION-LOG-MIB • NQA-MIB • OSPF-TRAP-MIB • P-BRIDGE-MIB • Q-BRIDGE-MIB • RFC1213-MIB • RIPv2-MIB • RMON2-MIB • RMON-MIB • SAVI-MIB • SNMP-FRAMEWORK-MIB • SNMP-MPD-MIB • SNMP-NOTIFICATION-MIB • SNMP-TARGET-MIB • SNMP-USER-BASED-SM-MIB • SNMPv2-MIB • TCP-MIB • UDP-MIB

Category	MIB
Huawei-proprietary MIB	• HUAWEI-AAA-MIB • HUAWEI-ACL-MIB • HUAWEI-ALARM-MIB • HUAWEI-ALARM-RELIABILITY-MIB • HUAWEI-BASE-TRAP-MIB • HUAWEI-BRAS-RADIUS-MIB • HUAWEI-BRAS-SRVCFG-EAP-MIB • HUAWEI-BRAS-SRVCFG-STATICUSER-MIB • HUAWEI-CBQOS-MIB • HUAWEI-CDP-COMPLIANCE-MIB • HUAWEI-CONFIG-MAN-MIB • HUAWEI-CPU-MIB • HUAWEI-DAD-TRAP-MIB • HUAWEI-DC-MIB • HUAWEI-DATASYNC-MIB • HUAWEI-DEVICE-MIB • HUAWEI-DHCPR-MIB • HUAWEI-DHCPS-MIB • HUAWEI-DHCP-SNOOPING-MIB • HUAWEI-DIE-MIB • HUAWEI-DNS-MIB • HUAWEI-DLDP-MIB • HUAWEI-ELMI-MIB • HUAWEI-ERPS-MIB • HUAWEI-ERRORDOWN-MIB • HUAWEI-ENERGYMNGT-MIB • HUAWEI-EASY-OPERATION-MIB • HUAWEI-ENTITY-EXTENT-MIB • HUAWEI-ENTITY-TRAP-MIB • HUAWEI-ETHARP-MIB • HUAWEI-ETHOAM-MIB • HUAWEI-FLASH-MAN-MIB • HUAWEI-FWD-RES-TRAP-MIB • HUAWEI-GARP-APP-MIB • HUAWEI-GTSM-MIB • HUAWEI-HGMP-MIB • HUAWEI-HWTACACS-MIB • HUAWEI-IF-EXT-MIB • HUAWEI-INFOCENTER-MIB • HUAWEI-IPPOOL-MIB • HUAWEI-IPV6-MIB • HUAWEI-ISOLATE-MIB • HUAWEI-L2IF-MIB • HUAWEI-L2MAM-MIB

Category	MIB
	• HUAWEI-L2VLAN-MIB • HUAWEI_LDT-MIB • HUAWEI-LLDP-MIB • HUAWEI-MAC-AUTHEN-MIB • HUAWEI-MEMORY-MIB • HUAWEI-MFF-MIB • HUAWEI-MFLP-MIB • HUAWEI-MSTP-MIB • HUAWEI-MULTICAST-MIB • HUAWEI-NAP-MIB • HUAWEI-NTPV3-MIB • HUAWEI-PERFORMANCE-MIB • HUAWEI-PORT-MIB • HUAWEI-PORTAL-MIB • HUAWEI-QINQ-MIB • HUAWEI-RIPv2-EXT-MIB • HUAWEI-RM-EXT-MIB • HUAWEI-RRPP-MIB • HUAWEI-SECURITY-MIB • HUAWEI-SEP-MIB • HUAWEI-SNMP-EXT-MIB • HUAWEI-SSH-MIB • HUAWEI-STACK-MIB • HUAWEI-SWITCH-L2MAM-EXT-MIB • HUAWEI-SWITCH-SRV-TRAP-MIB • HUAWEI-SYS-MAN-MIB • HUAWEI-TCP-MIB • HUAWEI-TFTPC-MIB • HUAWEI-TRNG-MIB • HUAWEI-XQOS-MIB

NOTE

For more information about MIBs supported by CloudEngine S6730-H-V2 series optical switches, visit: https://support.huawei.com/enterprise/en/switches/s6700-pid-6691593?category=reference-guides

Standards Compliance

The following table lists the standards that CloudEngine S6730-H-V2 series optical switches comply with.

Standard Organization	Standard or Protocol
IETF	• RFC 768 User Datagram Protocol (UDP) • RFC 792 Internet Control Message Protocol (ICMP) • RFC 793 Transmission Control Protocol (TCP) • RFC 826 Ethernet Address Resolution Protocol (ARP) • RFC 854 Telnet Protocol Specification • RFC 951 Bootstrap Protocol (BOOTP)

Standard Organization	Standard or Protocol
	• RFC 959 File Transfer Protocol (FTP) • RFC 1058 Routing Information Protocol (RIP) • RFC 1112 Host extensions for IP multicasting • RFC 1157 A Simple Network Management Protocol (SNMP) • RFC 1256 ICMP Router Discovery • RFC 1305 Network Time Protocol Version 3 (NTP) • RFC 1349 Internet Protocol (IP) • RFC 1493 Definitions of Managed Objects for Bridges • RFC 1542 Clarifications and Extensions for the Bootstrap Protocol • RFC 1643 Ethernet Interface MIB • RFC 1757 Remote Network Monitoring (RMON) • RFC 1901 Introduction to Community-based SNMPv2 • RFC 1902-1907 SNMP v2 • RFC 1981 Path MTU Discovery for IP version 6 • RFC 2131 Dynamic Host Configuration Protocol (DHCP) • RFC 2328 OSPF Version 2 • RFC 2453 RIP Version 2 • RFC 2460 Internet Protocol, Version 6 Specification (IPv6) • RFC 2461 Neighbor Discovery for IP Version 6 (IPv6) • RFC 2462 IPv6 Stateless Address Auto configuration • RFC 2463 Internet Control Message Protocol for IPv6 (ICMPv6) • RFC 2474 Differentiated Services Field (DS Field) • RFC 2475 An Architecture for Differentiated Services • RFC 2740 OSPF for IPv6 (OSPFv3) • RFC 2863 The Interfaces Group MIB • RFC 2597 Assured Forwarding PHB Group • RFC 2598 An Expedited Forwarding PHB • RFC 2571 SNMP Management Frameworks • RFC 2865 Remote Authentication Dial In User Service (RADIUS) • RFC 3046 DHCP Option82/Relay • RFC 3376 Internet Group Management Protocol, Version 3 (IGMPv3) • RFC 3513 IP Version 6 Addressing Architecture • RFC 3579 RADIUS Support For EAP • RFC 4271 A Border Gateway Protocol 4 (BGP-4) • RFC 4760 Multiprotocol Extensions for BGP-4 • draft-grant-tacacs-02 TACACS+ • RFC5340 OSPF for IPv6 • RFC 5798 Virtual Router Redundancy Protocol (VRRP) Version 3 for IPv4 and IPv6 • RFC 6241 Network Configuration Protocol (NETCONF) • RFC 6020 YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF) • RFC 7348 Virtual eXtensible Local Area Network (VXLAN): A Framework for Overlaying Virtualized Layer 2 Networks over Layer 3 Networks • RFC 8365 A Network Virtualization Overlay Solution Using Ethernet VPN (EVPN)

Standard Organization	Standard or Protocol
IEEE	• IEEE 802.1D Media Access Control (MAC) Bridges • IEEE 802.1p Traffic Class Expediting and Dynamic Multicast Filtering • IEEE 802.1Q Virtual Bridged Local Area Networks • IEEE 802.1ad Provider Bridges • IEEE 802.2 Logical Link Control • IEEE Std 802.3 CSMA/CD • IEEE Std 802.3ab 1000BASE-T specification • IEEE Std 802.3ad Aggregation of Multiple Link Segments • IEEE Std 802.3ae 10GE WEN/LAN Standard • IEEE Std 802.3x Full Duplex and flow control • IEEE Std 802.3z Gigabit Ethernet Standard • IEEE 802.1ax/IEEE802.3ad Link Aggregation • IEEE 802.3ah Ethernet in the First Mile. • IEEE 802.1ag Connectivity Fault Management • IEEE 802.1ab Link Layer Discovery Protocol • IEEE 802.1D Spanning Tree Protocol • IEEE 802.1w Rapid Spanning Tree Protocol • IEEE 802.1s Multiple Spanning Tree Protocol • IEEE 802.1x Port based network access control protocol • IEEE 802.3az Automatic power adjustment on Ethernet interfaces
ITU	• ITU SG13 Y.17ethoam • ITU SG13 QoS control Ethernet-Based IP Access • ITU-T Y.1731 ETH OAM performance monitor
ISO	• ISO 10589 IS-IS Routing Protocol
MEF	• MEF 2 Requirements and Framework for Ethernet Service Protection • MEF 9 Abstract Test Suite for Ethernet Services at the UNI • MEF 10.2 Ethernet Services Attributes Phase 2 • MEF 11 UNI Requirements and Framework • MEF 13 UNI Type 1 Implementation Agreement • MEF 15 Requirements for Management of Metro Ethernet Phase 1 Network Elements • MEF 17 Service OAM Framework and Requirements • MEF 20 UNI Type 2 Implementation Agreement • MEF 23 Class of Service Phase 1 Implementation Agreement • Xmodem XMODEM/YMODEM Protocol Reference

NOTE

The listed standards and protocols are fully or partially supported by Huawei switches. For details, visit http://e.huawei.com/en or contact your local Huawei sales office.

Ordering Information

The following table lists ordering information of CloudEngine S6730-H-V2 series optical switches.

Model	Product Description
CloudEngine S6730-H6FX4Y2CZ-V2	S6730-H6FX4Y2CZ-V2 (6*CFP2 PEN ports (a single CFP2 PEN port supports 16*10GE SFP+ channels), 4*25GE SFP28 ports, 2*100GE QSFP28 ports, expansion card slot, without power module)
HSIC-X08S000	Interface card with 8*10GE SFP+ ports or 4*25GE SFP28 ports (only ports 1 to 4 support 25GE)
HSIC-Y08S000	Interface card with 8*25GE SFP28 ports
HSIC-Q04S000	Interface card with 4*40GE QSFP ports or 2*100GE QSFP28 ports (only ports 1/3 support 100GE)
HSIC-C04S000	Interface card with 4*100GE QSFP28 ports
PDC400S12-CB	400W DC Power Module
PAC600S12-PB	600W AC &240 V DC Power Module
PAC1K2S12-PB	1200W AC&240V DC Power Module
PDC1K2S12-CE	1200W DC Power Module
FAN-031A-B	Fan Module

License	Product Description
N1-S67H-M-Lic	S67XX-H Series Basic SW, Per Device
N1-S67H-M-SnS1Y	S67XX-H Series Basic SW, SnS, Per Device,1Year
N1-S67H-F-Lic	N1-CloudCampus, Foundation, S67XX-H Series, Per Device
N1-S67H-F-SnS	N1-CloudCampus, Foundation, S67XX-H Series, SnS, Per Device
N1-S67H-A-Lic	N1-CloudCampus, Advanced, S67XX-H Series, Per Device
N1-S67H-A-SnS	N1-CloudCampus, Advanced, S67XX-H Series, SnS, Per Device
N1-S67H-FToA-Lic	N1-Upgrade-Foundation to Advanced, S67XX-H, Per Device
N1-S67H-FToA-SnS	N1-Upgrade-Foundation to Advanced, S67XX-H, SnS, Per Device
N1-AM-30-Lic	N1-CloudCampus, Add-On Package, Access Management, Per 30 Endpoints
N1-AM-30-SnS1Y	N1-CloudCampus, Add-On Package, Access Management, Software Subscription and Support, Per 30 Endpoints, 1 Year
N1-EPNP-30-Lic	N1-CloudCampus, Add-On Package, Endpoints Plug and Play, Per 30 Endpoints
N1-EPNP-30-SnS1Y	N1-CloudCampus, Add-On Package, Endpoints Plug and Play, Software Subscription and Support, Per 30 Endpoints, 1 Year
N1-APP-X7FSwitch	N1-CloudCampus, Add-On Package, Intelligent Application Analysis, X7 Series Fixed Switch, Per Device
N1-APP-X7FSwitch-SnS1Y	N1-CloudCampus, Add-On Package, Intelligent Application Analysis, X7 Series Fixed Switch, Software Subscription and Support, Per Device, 1 Year
N1-S67H-A-NVXLAN-Lic	N1-CloudCampus, Advanced non-vxlan, S67XX-H Series, Per Device
N1-S67H-A-NVXLAN-SnS1Y	N1-CloudCampus, Advanced non-vxlan, S67XX-H Series, SnS, Per Device,1 Year
N1-S67H-F2A-NVXLAN-Lic	N1-Upgrade-Foundation to Advanced non-vxlan, S67XX-H, Per Device
N1-S67H-F2A-NVXLAN-SnS1Y	N1-Upgrade-Foundation to Advanced non-vxlan, S67XX-H, SnS, Per Device,1 Year

More Information

For more information about the Huawei Campus Switches, visit http://e.huawei.com or contact us in the following ways:

- Global service hotline: http://e.huawei.com/en/service-hotline
- Logging in to the Huawei Enterprise technical support website: http://support.huawei.com/enterprise/
- Sending an email to the customer service mailbox: support_e@huawei. com

Copyright © Huawei Technologies Co., Ltd. 2026. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address:Huawei Industrial Base Bantian, Longgang Shenzhen 518129 People's Republic of China

Website:e.huawei.com