

2.5-in SSD DATA SHEET

Lightspeed. Solid. Impressive.

Consistent high performance for the modern data center.

The Seagate® Nytro® 5050 series NVMe solid state drive represents the next generation of enterprise SSDs. Engineered for efficiency, high performance, and increased storage density in data centers, Nytro 5050 SSD eliminates performance bottlenecks and significantly improves quality of service (QoS).



Best-Fit Applications

- Server virtualization
- OLTP databases
- Software-defined storage
- All-flash arrays
- Caching and tiering

Best-in-class performance—PCIe Gen4 NVMe SSD doubles the random throughput of the latest SAS SSDs, achieving over ten times the bandwidth of SATA.

Blistering 7.4GB/s bandwidth and up to 1.7M IOPS removes data bottlenecks and provides consistent response times.

Boosted capacity in ultra-dense environments—up to 15TB¹ supporting U.2 and U.3 interface, and dual ports support active active high availability.

Highly optimized, the Nytro 5350 withstands read-intensive workloads while the Nytro 5550 is built to endure mixed workloads.

Single or dual interface The 5350 has the choice between dual or single interface that meet your needs.

Quintupled performance over SATA SSDs with 10x more bandwidth and IOPS over previous generations to get more computing using minimal space, energy, and cost.

Low latency and high quality of service deliver improved responsiveness and enhanced user experience.

Effortless serviceability and maintenance with no downtime requirements, and hot-swap capability for easy SSD addition, removal, or replacement.

Hardware-based encryption Self-Encrypting Drive (SED) models² support the TCG standard to help keep valuable data secure.

Operating system friendly to easily integrate with Linux and Microsoft.

Enhanced durability and reliability with 1 and 3 DWPD at 2.5M MTBF—move massive enterprise data for the long haul.

1 Available soon. For more information, contact your Seagate sales representative.

2 Self-Encrypting Drives (SED) are not available in all models or countries. May require TCG-compliant host or controller support.



Specifications					
Nytro 5550H 15mm—Mixed Use					
Capacity	12.8TB	6.4TB	3.2TB	1.6TB	800GB
Standard Model	XP12800LE70005	XP6400LE70005	XP3200LE70005	XP1600LE70005	XP800LE70005
SED Model	XP12800LE70015	XP6400LE70015	XP3200LE70015	XP1600LE70015	XP800LE70015
FIPS 140-3/Common Criteria Model	XP12800LE70025	XP6400LE70025	XP3200LE70025	XP1600LE70025	XP800LE70025
Features					
Interface (Single Port)	-	-	-	-	-
Interface (Dual Port)	PCIe® Gen4 x4 NVMe				
NAND Flash Type	3D eTLC				
Form Factor	2.5 in x 15mm				
Performance					
Sequential Read (MB/s) Sustained, 128KB ²	7400MB/s	7400MB/s	7400MB/s	7400MB/s	7400MB/s
Sequential Write (MB/s) Sustained, 128KB ²	7200	7200	6900	3700	1900
Random Read (IOPS) Sustained, 4KB ³	1,700,000	1,700,000	1,700,000	1,550,000	945,000
Random Write (IOPS) Sustained, 4KB ³	495,000	445,000	460,000	315,000	140,000
Average Read Latency (µs), 4KB QD1	75	75	75	75	75
Average Write Latency (µs), 4KB QD1	12	12	12	12	12
Endurance/Reliability					
Lifetime Endurance (Drive Writes per Day)	3	3	3	3	3
Total Bytes Written (TB)	70,000	35,000	17,500	8,700	4,300
Nonrecoverable Read Errors per Bits Read	1 per 10E17				
Mean Time Between Failures (MTBF, hours)	2500000hr	2500000hr	2500000hr	2500000hr	2500000hr
Limited Warranty (years)	5	5	5	5	5
Power Management					
12V Overall Average Active Power (W)	23	21	20	15	11
Average Idle Power (W)	7W	6W	6W	6W	5W
Environmental					
Temperature, Operating Internal (°C)	0 to 70				
Temperature, Nonoperating (°C)	-40°C – 85°C				
Temperature Change Rate/Hr, Max (°C)	30°C per hour				
Shock, 0.5ms (Gs)	1500Gs	1500Gs	1500Gs	1500Gs	1500Gs
Physical					
Height (mm/in, max)	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in
Width (mm/in, max)	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in
Depth (mm/in, max)	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in
Weight (g/lb, max)	170g/0.38lb	205g/0.45lb	205g/0.45lb	205g/0.45lb	205g/0.45lb
Carton Unit Quantity	10	10	10	10	10

1 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

2 Sequential performance measured at queue depth of 32 at beginning of life. System application performance may vary based on host and prior system workload.

3 Random performance measured at queue depth of 256 at beginning of life. System application performance may vary based on host and prior system workload.



Nytro 5350H 15mm—Read Intensive				
Capacity	15.36TB	7.68TB	3.84TB	1.92TB
Standard Model	XP15360SE70005	XP7680SE70005	XP3840SE70005	XP1920SE70005
SED Model	XP15360SE70015	XP7680SE70015	XP3840SE70015	XP1920SE70015
FIPS 140-3/Common Criteria Model	XP15360SE70025	XP7680SE70025	XP3840SE70025	XP1920SE70025
Features				
Interface (Single Port)	-	-	-	-
Interface (Dual Port)	PCIe® Gen4 x4 NVMe			
NAND Flash Type	3D eTLC	3D eTLC	3D eTLC	3D eTLC
Form Factor	2.5 in x 15mm			
Performance				
Sequential Read (MB/s) Sustained, 128KB ²	7400MB/s	7400MB/s	7400MB/s	7400MB/s
Sequential Write (MB/s) Sustained, 128KB ²	7200	7200	6900	3700
Random Read (IOPS) Sustained, 4KB ³	1,700,000	1,700,000	1,700,000	1,550,000
Random Write (IOPS) Sustained, 4KB ³	195,000	195,000	195,000	125,000
Average Read Latency (µs), 4KB QD1	75	75	75	75
Average Write Latency (µs), 4KB QD1	12	12	12	12
Endurance/Reliability				
Lifetime Endurance (Drive Writes per Day)	1	1	1	1
Total Bytes Written (TB)	28,000	14,000	7,000	3,500
Nonrecoverable Read Errors per Bits Read	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17
Mean Time Between Failures (MTBF, hours)	2500000hr	2500000hr	2500000hr	2500000hr
Limited Warranty (years)	5	5	5	5
Power Management				
12V Overall Average Active Power (W)	23	21	20	15
Average Idle Power (W)	7W	6W	6W	6W
Environmental				
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70	0 to 70
Temperature, Nonoperating (°C)	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C
Temperature Change Rate/Hr, Max (°C)	30°C per hour	30°C per hour	30°C per hour	30°C per hour
Shock, 0.5ms (Gs)	1500Gs	1500Gs	1500Gs	1500Gs
Physical				
Height (mm/in, max)	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in
Width (mm/in, max)	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in
Depth (mm/in, max)	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in
Weight (g/lb, max)	170g/0.38lb	205g/0.45lb	205g/0.45lb	205g/0.45lb
Carton Unit Quantity	10	10	10	10

1 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

2 Sequential performance measured at queue depth of 32 at beginning of life. System application performance may vary based on host and prior system workload.

3 Random performance measured at queue depth of 256 at beginning of life. System application performance may vary based on host and prior system workload.



Nytro 5550M 15mm—Mixed Use					
Capacity	12.8TB	6.4TB	3.2TB	1.6TB	800GB
Standard Model	XP12800LE70035	XP6400LE70035	XP3200LE70035	XP1600LE70035	XP800LE70035
SED Model	XP12800LE70045	XP6400LE70045	XP3200LE70045	XP1600LE70045	XP800LE70045
FIPS 140-3/Common Criteria Model	XP12800LE70055	XP6400LE70055	XP3200LE70055	XP1600LE70055	XP800LE70055
Features					
Interface (Single Port)	-	-	-	-	-
Interface (Dual Port)	PCIe® Gen4 x4 NVMe				
NAND Flash Type	3D eTLC				
Form Factor	2.5 in x 15mm				
Performance					
Sequential Read (MB/s) Sustained, 128KB ²	7400MB/s	7400MB/s	7400MB/s	7400MB/s	7200MB/s
Sequential Write (MB/s) Sustained, 128KB ²	4500	4500	4500	3300	1900
Random Read (IOPS) Sustained, 4KB ³	1,250,000	1,250,000	1,250,000	1,250,000	1,000,000
Random Write (IOPS) Sustained, 4KB ³	290,000	330,000	350,000	240,000	140,000
Average Read Latency (μs), 4KB QD1	90	90	90	90	90
Average Write Latency (μs), 4KB QD1	12	12	12	12	12
Endurance/Reliability					
Lifetime Endurance (Drive Writes per Day)	3	3	3	3	3
Total Bytes Written (TB)	70,000	35,000	17,500	8,700	4,300
Nonrecoverable Read Errors per Bits Read	1 per 10E17				
Mean Time Between Failures (MTBF, hours)	2500000hr	2500000hr	2500000hr	2500000hr	2500000hr
Limited Warranty (years)	5	5	5	5	5
Power Management					
12V Overall Average Active Power (W)	16	15	14	11	9
Average Idle Power (W)	7W	6W	6W	5W	5W
Environmental					
Temperature, Operating Internal (°C)	0 to 70				
Temperature, Nonoperating (°C)	-40°C – 85°C				
Temperature Change Rate/Hr, Max (°C)	30°C per hour				
Shock, 0.5ms (Gs)	1500Gs	1500Gs	1500Gs	1500Gs	1500Gs
Physical					
Height (mm/in, max)	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in
Width (mm/in, max)	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in
Depth (mm/in, max)	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in
Weight (g/lb, max)	170g/0.38lb	205g/0.45lb	205g/0.45lb	205g/0.45lb	205g/0.45lb
Carton Unit Quantity	10	10	10	10	10

1 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

2 Sequential performance measured at queue depth of 32 at beginning of life. System application performance may vary based on host and prior system workload.

3 Random performance measured at queue depth of 256 at beginning of life. System application performance may vary based on host and prior system workload.



Nytro 5350M 15mm—Read Intensive				
Capacity	15.36TB	7.68TB	3.84TB	1.92TB
Standard Model	XP15360SE70035	XP7680SE70035	XP3840SE70035	XP1920SE70035
SED Model	XP15360SE70045	XP7680SE70045	XP3840SE70045	XP1920SE70045
FIPS 140-3/Common Criteria Model	XP15360SE70055	XP7680SE70055	XP3840SE70055	XP1920SE70055
Features				
Interface (Single Port)	-	-	-	-
Interface (Dual Port)	PCIe® Gen4 x4 NVMe			
NAND Flash Type	3D eTLC	3D eTLC	3D eTLC	3D eTLC
Form Factor	2.5 in x 15mm			
Performance				
Sequential Read (MB/s) Sustained, 128KB ²	7400MB/s	7400MB/s	7400MB/s	7400MB/s
Sequential Write (MB/s) Sustained, 128KB ²	4500	4500	4500	3300
Random Read (IOPS) Sustained, 4KB ³	1,250,000	1,250,000	1,250,000	1,250,000
Random Write (IOPS) Sustained, 4KB ³	140,000	140,000	140,000	90,000
Average Read Latency (µs), 4KB QD1	90	90	90	90
Average Write Latency (µs), 4KB QD1	12	12	12	12
Endurance/Reliability				
Lifetime Endurance (Drive Writes per Day)	1	1	1	1
Total Bytes Written (TB)	28,000	14,000	7,000	3,500
Nonrecoverable Read Errors per Bits Read	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17
Mean Time Between Failures (MTBF, hours)	2500000hr	2500000hr	2500000hr	2500000hr
Limited Warranty (years)	5	5	5	5
Power Management				
12V Overall Average Active Power (W)	16	15	14	11
Average Idle Power (W)	7W	6W	6W	6W
Environmental				
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70	0 to 70
Temperature, Nonoperating (°C)	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C
Temperature Change Rate/Hr, Max (°C)	30°C per hour	30°C per hour	30°C per hour	30°C per hour
Shock, 0.5ms (Gs)	1500Gs	1500Gs	1500Gs	1500Gs
Physical				
Height (mm/in, max)	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in
Width (mm/in, max)	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in
Depth (mm/in, max)	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in
Weight (g/lb, max)	170g/0.38lb	205g/0.45lb	205g/0.45lb	205g/0.45lb
Carton Unit Quantity	10	10	10	10

1 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

2 Sequential performance measured at queue depth of 32 at beginning of life. System application performance may vary based on host and prior system workload.

3 Random performance measured at queue depth of 256 at beginning of life. System application performance may vary based on host and prior system workload.



Nytro 5550M 7mm—Mixed Use				
Capacity	6.4TB	3.2TB	1.6TB	800GB
Standard Model	XP6400LE10005	XP3200LE10005	XP1600LE10005	XP800LE10005
SED Model	XP6400LE10015	XP3200LE10015	XP1600LE10015	XP800LE10015
FIPS 140-3/Common Criteria Model	XP6400LE10025	XP3200LE10025	XP1600LE10025	XP800LE10025
Features				
Interface (Single Port)	-	-	-	-
Interface (Dual Port)	PCIe® Gen4 x4 NVMe			
NAND Flash Type	3D eTLC	3D eTLC	3D eTLC	3D eTLC
Form Factor	2.5 in x 7mm			
Performance				
Sequential Read (MB/s) Sustained, 128KB ²	7400MB/s	7400MB/s	7400MB/s	7200MB/s
Sequential Write (MB/s) Sustained, 128KB ²	6000	6000	3200	1900
Random Read (IOPS) Sustained, 4KB ³	1,250,000	1,250,000	1,250,000	1,000,000
Random Write (IOPS) Sustained, 4KB ³	360,000	360,000	230,000	140,000
Average Read Latency (µs), 4KB QD1	90	90	90	90
Average Write Latency (µs), 4KB QD1	12	12	12	12
Endurance/Reliability				
Lifetime Endurance (Drive Writes per Day)	3	3	3	3
Total Bytes Written (TB)	35,000	17,500	8,700	4,300
Nonrecoverable Read Errors per Bits Read	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17
Mean Time Between Failures (MTBF, hours)	2500000hr	2500000hr	2500000hr	2500000hr
Limited Warranty (years)	5	5	5	5
Power Management				
12V Overall Average Active Power (W)	18	17	11	8
Average Idle Power (W)	5W	5W	5W	5W
Environmental				
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70	0 to 70
Temperature, Nonoperating (°C)	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C
Temperature Change Rate/Hr, Max (°C)	30°C per hour	30°C per hour	30°C per hour	30°C per hour
Shock, 0.5ms (Gs)	1500Gs	1500Gs	1500Gs	1500Gs
Physical				
Height (mm/in, max)	7.1mm/0.280in	7.1mm/0.280in	7.1mm/0.280in	7.1mm/0.280in
Width (mm/in, max)	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in
Depth (mm/in, max)	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in
Weight (g/lb, max)	105g/0.23lb	105g/0.23lb	105g/0.23lb	105g/0.23lb
Carton Unit Quantity	10	10	10	10

1 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

2 Sequential performance measured at queue depth of 32 at beginning of life. System application performance may vary based on host and prior system workload.

3 Random performance measured at queue depth of 256 at beginning of life. System application performance may vary based on host and prior system workload.



Nytre 5350M 7mm—Read Intensive			
Capacity	7.68TB	3.84TB	1.92TB
Standard Model	XP7680SE10005	XP3840SE10005	XP1920SE10005
SED Model	XP7680SE10015	XP3840SE10015	XP1920SE10015
FIPS 140-3/Common Criteria Model	XP7680SE10025	XP3840SE10025	XP1920SE10025
Features			
Interface (Single Port)	-	-	-
Interface (Dual Port)	PCIe® Gen4 x4 NVMe	PCIe® Gen4 x4 NVMe	PCIe® Gen4 x4 NVMe
NAND Flash Type	3D eTLC	3D eTLC	3D eTLC
Form Factor	2.5 in x 7mm	2.5 in x 7mm	2.5 in x 7mm
Performance			
Sequential Read (MB/s) Sustained, 128KB ²	7400MB/s	7400MB/s	7400MB/s
Sequential Write (MB/s) Sustained, 128KB ²	6000	6000	3200
Random Read (IOPS) Sustained, 4KB ³	1,250,000	1,250,000	1,250,000
Random Write (IOPS) Sustained, 4KB ³	150,000	160,000	100,000
Average Read Latency (μs), 4KB QD1	90	90	90
Average Write Latency (μs), 4KB QD1	12	12	12
Endurance/Reliability			
Lifetime Endurance (Drive Writes per Day)	1	1	1
Total Bytes Written (TB)	14,000	7,000	3,500
Nonrecoverable Read Errors per Bits Read	1 per 10E17	1 per 10E17	1 per 10E17
Mean Time Between Failures (MTBF, hours)	2500000hr	2500000hr	2500000hr
Limited Warranty (years)	5	5	5
Power Management			
12V Overall Average Active Power (W)	18	16	11
Average Idle Power (W)	5W	5W	5W
Environmental			
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70
Temperature, Nonoperating (°C)	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C
Temperature Change Rate/Hr, Max (°C)	30°C per hour	30°C per hour	30°C per hour
Shock, 0.5ms (Gs)	1500Gs	1500Gs	1500Gs
Physical			
Height (mm/in, max)	7.1mm/0.280in	7.1mm/0.280in	7.1mm/0.280in
Width (mm/in, max)	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in
Depth (mm/in, max)	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in
Weight (g/lb, max)	105g/0.23lb	105g/0.23lb	105g/0.23lb
Carton Unit Quantity	10	10	10

1 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

2 Sequential performance measured at queue depth of 32 at beginning of life. System application performance may vary based on host and prior system workload.

3 Random performance measured at queue depth of 256 at beginning of life. System application performance may vary based on host and prior system workload.



Nytre 5350S 15mm—Read Intensive				
Capacity	15.36TB	7.68TB	3.84TB	1.92TB
Standard Model	XP15360SE70065	XP7680SE70065	XP3840SE70065	XP1920SE70065
SED Model	XP15360SE70075	XP7680SE70075	XP3840SE70075	XP1920SE70075
FIPS 140-3/Common Criteria Model	—	—	—	—
Features				
Interface (Single Port)	PCIe Gen4 x4 NVMe			
Interface (Dual Port)	—	—	—	—
NAND Flash Type	3D eTLC	3D eTLC	3D eTLC	3D eTLC
Form Factor	2.5 in x 15mm			
Performance				
Sequential Read (MB/s) Sustained, 128KB ²	7400MB/s	7400MB/s	7400MB/s	7400MB/s
Sequential Write (MB/s) Sustained, 128KB ²	7200	7200	6900	3700
Random Read (IOPS) Sustained, 4KB ³	1,700,000	1700000	1,700,000	1,550,000
Random Write (IOPS) Sustained, 4KB ³	195,000	195,000	195,000	125,000
Average Read Latency (μs), 4KB QD1	75	75	75	75
Average Write Latency (μs), 4KB QD1	12	12	12	12
Endurance/Reliability				
Lifetime Endurance (Drive Writes per Day)	1	1	1	1
Total Bytes Written (TB)	28,000	14,000	7,000	3,500
Nonrecoverable Read Errors per Bits Read	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17
Mean Time Between Failures (MTBF, hours)	2500000hr	2500000hr	2500000hr	2500000hr
Limited Warranty (years)	5	5	5	5
Power Management				
12V Overall Average Active Power (W)	23	21	20	15
Average Idle Power (W)	7W	6W	6W	6W
Environmental				
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70	0 to 70
Temperature, Nonoperating (°C)	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C
Temperature Change Rate/Hr, Max (°C)	30°C per hour	30°C per hour	30°C per hour	30°C per hour
Shock, 0.5ms (Gs)	1300	1300	1300	1300
Physical				
Height (mm/in, max)	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in	14.9mm/0.587in
Width (mm/in, max)	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in	70.1mm/2.760in
Depth (mm/in, max)	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in	100.4mm/3.953in
Weight (g/lb, max)	170g/0.38lb	205g/0.45lb	205g/0.45lb	205g/0.45lb
Carton Unit Quantity	10	10	10	10

1 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

2 Sequential performance measured at queue depth of 32 at beginning of life. System application performance may vary based on host and prior system workload.

3 Random performance measured at queue depth of 256 at beginning of life. System application performance may vary based on host and prior system workload.

seagate.com



© 2023 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Nytre, the Nytre logo, Seagate Secure, and the Seagate Secure logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The NVMe word mark and/or NVMeExpress design mark are trademarks of NVMeExpress, Inc. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import, and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS2099.3-2303US