


NVIDIA BlueField-2 DPU

Data center infrastructure on a chip.



By combining the industry-leading NVIDIA ConnectX®-6 Dx network adapter with an array of Arm® cores and infrastructure-specific offloads, BlueField-2 offers purpose-built hardware-acceleration engines with full software programmability. Sitting at the edge of every server, BlueField-2 empowers agile, secure, and high-performance cloud and artificial intelligence (AI) workloads, all while reducing the total cost of ownership and increasing data center efficiency.

The NVIDIA DOCA™ software framework enables developers to rapidly create applications and services for the BlueField-2 DPU. NVIDIA DOCA makes it easy to leverage DPU hardware accelerators, providing breakthrough data center performance, efficiency, and security.

Key Software-Defined, Hardware-Accelerated Applications



Networking

vSwitch/vRouter, NAT, load balancer, NFV



Storage

NVMe[™] over fabrics (NVMe-oF[™]), elastic storage virtualization, hyperconverged infrastructure (HCI), encryption, data integrity, compression, data deduplication



Security

Next-generation firewall, root of trust, micro-segmentation, DDOS prevention



Key Features

Security

- > Hardened isolation layer
- > Hardware root of trust
- > IPsec/TLS and AES-XTS encryption acceleration
- Connection tracking for stateful firewall

Storage

- > NVIDIA GPUDirect® Storage
- Elastic block storage enabled by BlueField SNAP storage virtualization
- Compression and decompression acceleration
- > NVMe-oF acceleration
- > Virtio-blk acceleration

Features

Network and Host Interfaces

Network Interfaces

- > Ethernet—Dual ports of 10/25/50/100Gb/s, or a single port of 200Gb/s
- > InfiniBand—Dual ports of EDR/ HDR100, or a single port of HDR

PCI Express Interface

- > 8 or 16 lanes of PCle Gen 4.0
- > PCle switch bi-furcation with 8 downstream ports

ARM/DDR Subsystem

Arm Cores

- > Up to 8 Armv8 A72 cores (64-bit) pipeline
- > 1MB L2 cache per 2 cores
- > 6MB L3 cache with plurality of eviction policies

DDR4 DIMM Support

- > Single DDR4 DRAM controller
- > 16GB/32GB of onboard DDR4
- > ECC error protection support

Hardware Accelerations

Security

- > Secure boot with hardware root-of-trust
 - · Secure firmware update
 - · Cerberus compliant
- > IPsec/TLS data-in-motion encryption (AES-GCM 128/256-bit key)
- > AES-XTS 256/512-bit data-at-rest encryption

- > SHA 256-bit hardware acceleration
- > Hardware public key accelerator
 - · RSA, Diffie-Hellman, DSA, ECC, EC-DSA, EC-DH
- > True random number generator (TRNG)

Storage

- > BlueField SNAP—NVMe and Virtio-blk
- > NVMe-oF acceleration
- > Compression and decompression acceleration
- > Data hashing and deduplication

Networking

- > RoCE, Zero Touch RoCE
- > Stateless offloads for:
 - TCP/UDP/IP
 - LSO/LRO/checksum/RSS/TSS/HDS
 - · VLAN insertion/stripping
- > SR-IOV
- > VirtIO-net
- > Multifunction per port
- > VMware NetQueue support
- > Virtualization hierarchies
- > 1K ingress and egress QoS levels

Boot Options

- > Secure boot (RSA authenticated)
- > Remote boot over Ethernet
- > Remote boot over iSCSI
- > PXE and UEFI

Networking

- > RoCE. Zero Touch RoCE
- > GPUDirect RDMA
- > SDN acceleration powered by NVIDIA ASAP² Accelerated Switching and Packet Processing™
- > Overlay network offloads including VXLAN

Management

- > Authenticated product life-cycle management
- > Telemetry agents

Portfolio

- > Dual ports of up to 100Gb/s, or a single port of 200Gb/s Ethernet or InfiniBand
- > 16GB/32GB of onboard DDR4 memory
- > Card form factors: HHHL, and FHHL
- > 1GbE out-of-band management port

Management

- > 1GbE out-of-band management port
- NC-SI, MCTP over SMBus, and MCT over PCIe
- > PLDM for Monitor and Control DSP0248
- > PLDM for Firmware Update DSP026
- > I²C interface for device control and configuration
- > SPI interface to flash
- > eMMC memory controller
- > UART
- > USB

Ordering Information

For NVIDIA ordering information, please contact your NVIDIA sales representative or visit our NVIDIA BlueField-2 User Guide index page:

- > NVIDIA BlueField-2 Ethernet boards
- > NVIDIA BlueField-2 InfiniBand/VPI boards



BlueField-2 DPU - 2x 25Gb/s HHHL form factor



BlueField-2 DPU - 2x 100Gb/s FHHL form factor



BlueField-2 DPU - 1x 200Gb/s HHHL form factor

Ready to Get Started?

To learn more about NVIDIA BlueField-2, visit nvidia.com/dpu

For information about NVIDIA support packages, please contact your NVIDIA sales representative or visit our **Support Index page**

© 2024 NVIDIA Corporation and affiliates. All rights reserved. NVIDIA, the NVIDIA logo, Accelerated Switch and Packet Processing (ASAP²), BlueField, ConnectX, DOCA, and GPUDirect are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated. All other trademarks are property of their respective owners.

ARM, AMBA, and ARM Powered are registered trademarks of ARM Limited. Cortex, MPCore and Mali are trademarks of ARM Limited. "ARM" is used to represent ARM Holdings plc; its operating company ARM Limited; and the regional subsidiaries ARM Inc.; ARM KK; ARM Korea Limited.; ARM Taiwan Limited; ARM France SAS; ARM Consulting (Shanghai) Co. Ltd.; ARM Germany GmbH; ARM Embedded Technologies Pvt. Ltd.; ARM Norway, AS and ARM Sweden AB. 3546650. DEC24

