


# G593-ZD2-AAX1

HPC/AI Server - 5U DP NVIDIA HGX™ H100 8-GPU 4-Root Port



## Key Features

- **NVIDIA-Certified Systems™ - Data Center Servers**
- NVIDIA HGX™ H100 8-GPU
- 900GB/s GPU-to-GPU bandwidth with NVIDIA NVLink™ and NVSwitch™
- Dual AMD EPYC™ 9005/9004 Series Processors
- 12-Channel DDR5 RDIMM, 24 x DIMMs
- Dual ROM Architecture
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 2 x M.2 slots with PCIe Gen3 x4 and x1 interface
- 8 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 4 x FHHL PCIe Gen5 x16 slots
- 8 x LP PCIe Gen5 x16 slots
- 5+1 3000W 80 PLUS Titanium redundant power supplies

## Applications

AI Platform, AI Training Server, AI Inference Server, High-Performance Computing Server...

## Specification

<b>Dimensions</b>	5U (W447 x H219.7 x D945 mm)	<b>Modular GPU</b>	NVIDIA HGX™ H100 with 8 x SXM5 GPUs
<b>Motherboard</b>	MZB3-G43	<b>PCIe Expansion Slots</b>	4 x FHHL PCIe Gen5 x16 8 x LP PCIe Gen5 x16
<b>CPU</b>	AMD EPYC™ 9005 Series Processors AMD EPYC™ 9004 Series Processors Dual processor, cTDP up to 400W - At 25°C ambient, cTDP up to 500W	<b>I/O Ports</b>	<b>Front:</b> 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN (default) <b>Rear:</b> 1 x MLAN
<b>OS Compatibility</b>	<a href="#">OS Support List</a>	<b>Backplane Board</b>	PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
<b>Socket</b>	2 x LGA 6096 (Socket SP5)	<b>TPM</b>	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
<b>Chipset</b>	System on Chip	<b>Power Supply</b>	5+1 3000W 80 PLUS Titanium redundant power supplies AC Input: 100-240V  *The system power supply requires C19 power cord.
<b>Memory</b>	12-Channel DDR5 RDIMM, 24 x DIMMs [EPYC 9005] Up to 6400 MT/s [EPYC 9004] Up to 4800 MT/s	<b>System Management</b>	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
<b>LAN</b>	<b>Front:</b> 2 x 10Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mbps Management LAN <b>Rear:</b> 1 x 10/100/1000 Mbps Management LAN	<b>System Fans</b>	Motherboard: 2 x 40x40x56mm 4 x 60x60x56mm PCIe slots: 4 x 40x40x28mm 2 x 40x40x56mm GPU tray: 6 x 60x60x76mm 11 x 80x80x80mm
<b>Video</b>	Integrated in ASPEED® AST2600 - 1 x VGA port	<b>Operating Properties</b>	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
<b>Storage</b>	<b>Front hot-swap:</b> 8 x 2.5" Gen5 NVMe/SATA/SAS-4 <sup>[1]</sup> <b>Internal M.2:</b> 1 x M.2 (2280/22110), PCIe Gen3 x4 1 x M.2 (2280/22110), PCIe Gen3 x1  <sup>[1]</sup> Storage card is required to support SATA and SAS drives.	<b>Packaging Content</b>	1 x G593-ZD2-AAX1 2 x CPU heatsinks 1 x L-shape Rail kit
<b>RAID</b>	Require RAID add-in cards	<b>Ordering Part Numbers</b>	6NG593ZD2DR000ACX1*



Learn more at: <https://www.gigabyte.com/Enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

