

# Intel<sup>®</sup> Ethernet Network Adapter X710-T2L/T4L for OCP 3.0

Dual and quad-port energy-efficient OCP NIC 3.0  
adapters for NBASE-T and 10GBASE-T networks



## Key Features

- OCP NIC 3.0 Small Form Factor
- Energy Efficient Ethernet (EEE) / IEEE 802.3az enabled
- Backward compatible with multi-speed support for 1G, 10GBASE-T, and 100BASE-TX
- PCI Express (PCIe v3.0 x8)
- Network Virtualization offloads including VXLAN, GENEVE, NVGRE, MPLS, and VXLAN-GPE with Network Service Headers (NSH)
- Intel<sup>®</sup> Ethernet Flow Director for hardware based application traffic steering
- Dynamic Device Personalization (DDP) enables increased packet processing efficiency for NFV and Cloud deployments
- Data Plane Development Kit (DPDK) optimized for efficient packet processing
- Excellent small packet performance for network appliances and Network Functions Virtualization (NFV)
- I/O virtualization innovations for maximum performance in a virtualized server

## Overview

Simplify technology transitions with the Intel<sup>®</sup> Ethernet Network Adapter X710-T2L and X710-T4L for OCP 3.0. Auto-negotiation between port speeds provides maximum flexibility in dual and quad-port 10GBASE-T configurations. These low-power adapters also support Energy Efficient Ethernet to efficiently reduce power consumption during periods of low data activity.

The Intel<sup>®</sup> Ethernet Network Adapter X710-T2L and X710-T4L for OCP 3.0 are part of the Intel<sup>®</sup> Ethernet 700 Series, the foundation for server connectivity; providing broad interoperability, critical performance optimizations, and increased agility for Communications, Cloud, and Enterprise IT network solutions.

- **Interoperability** - Multiple speeds and media types for broad compatibility backed by extensive testing and validation.
- **Optimization** - Intelligent offloads and accelerators to unlock network performance in servers with Intel<sup>®</sup> Xeon<sup>®</sup> processors.
- **Agility** - Both Kernel and Data Plane Development Kit (DPDK) drivers for scalable packet processing.

The OCP NIC 3.0 specification defines a standardized design for a new generation of network adapters. Simple and straightforward form factors, clear manageability requirements, and improved serviceability help simplify deployment for current and emerging capabilities.

## All Intel® Ethernet 700 Series Network Adapters include these feature-rich technologies:

### Flexible and Scalable I/O for Virtualized Infrastructures

Intel® Virtualization Technology (Intel® VT), delivers outstanding I/O performance in virtualized server environments.

I/O bottlenecks are reduced through intelligent offloads such as Virtual Machine Device Queues (VMDq) and Flexible Port Partitioning, using SR-IOV with a common Virtual Function driver for networking traffic per Virtual Machine (VM), enabling near-native performance and VM scalability. Host-based features supported include:

**VMDq for Emulated Path:** VMDq, enables a hypervisor to represent a single network port as multiple network ports that can be assigned to the individual VMs. Traffic handling is offloaded to the network controller, delivering the benefits of port partitioning with little to no administrative overhead by the IT staff.

**SR-IOV for Direct Assignment:** Adapter-based isolation and switching for various virtual station instances enables optimal CPU usage in virtualized environments.

- Up to 128 VFs, each VF can support a unique and separate data path for I/O related functions within the PCI Express hierarchy.
- Use of SR-IOV with a networking device, for example, allows the bandwidth of a single port (function) to be partitioned into smaller slices that can be allocated to specific VMs or guests, via a standard interface.

**Intel® Ethernet Adaptive Virtual Function (Intel® Ethernet AVF):** Customers deploying mass-scale VMs or containers for their network infrastructure now have a common Virtual Function (VF) driver. This driver eases SR-IOV hardware upgrades or changes, preserves base mode functionality in hardware and software, and supports an advanced set of features in the Intel® Ethernet 700 Series.

### Enhanced Network Virtualization Overlays (NVO)

Network virtualization has changed the way networking is done in the data center, delivering accelerations across a wide range of tunneling methods.

VXLAN, GENEVE, NVGRE, MPLS, and VXLAN-GPE with NSH Offloads: These stateless offloads preserve application performance for overlay networks, and the network traffic can be distributed across CPU cores, increasing network throughput.

### Flexible Port Partitioning (FPP)

FPP leverages the PCI-SIG SR-IOV specification. Virtual controllers can be used by the Linux host directly and/or assigned to virtual machines.

- Assign up to 63 Linux host processes or virtual machines per port to virtual functions.
- Control the partitioning of per port bandwidth across multiple dedicated network resources, ensuring balanced QoS by giving each assigned virtual controller equal access to the ports bandwidth.

Network administrators can also rate limit each of these services to control how much of the pipe is available to each process.

### Greater Intelligence and Performance for NFV and Cloud deployments

Dynamic Device Personalization (DDP) customizable packet filtering, along with enhanced Data Plane Development Kit (DPDK), support advanced packet forwarding and high efficient packet processing for both Cloud and Network Functions Virtualization (NFV) workloads.

- DDP enables workload-specific optimizations, using the programmable packet-processing pipeline. Additional protocols can be added to the default set to improve packet processing efficiency that results in higher throughput and reduced latency. With the 700 Series, new protocols can be added or modified on-demand, and applied at run-time using Software Defined Firmware or APIs, eliminating the need to reset or reboot the server. This not only keeps the server and VMs up, running, and computing, it also increases performance for Virtual Network Functions (VNFs) that process network traffic that is not included in the default firmware. [Download DDP Profiles](#)
- DPDK provides a programming framework for Intel® processors and enables faster development of high-speed data packet networking applications.

### Advanced Traffic Steering

Intel® Ethernet Flow Director (Intel® Ethernet FD) is an advanced traffic steering capability built into the adapter. It consists of a large number of flow affinity filters that direct receive packets by their flows to queues for classification, load balancing, and matching between flows and CPU cores.

Steering traffic into specific queues can eliminate context switching required within the CPU. As a result, Intel® Ethernet FD significantly increases the number of transactions per second and reduces latency for cloud applications like memcached.

### Software Tools and Management

Intel® Ethernet Network Adapters support Dell's Lifecycle Controller. The Lifecycle Controller is coupled with the Dell Remote Access Card (DRAC) service processor to provide embedded system management. The Lifecycle Controller enables both local and remote access to manage initial setup and configuration of the BIOS settings on the platform, setup, and configuration of Intel Ethernet adapters, update of all the platform firmware, and the deployment of the operating systems.

Intel® Advanced Network Services (Intel® ANS) include new teaming technologies and techniques such as Virtual Machine Load-Balancing (VMLB) for Hyper-V environments. Intel ANS also provides a variety of teaming configurations for up to eight ports, and support for teaming mixed vendors' server adapters. Intel ANS includes support for 802.1Q VLANs, making Intel ANS one of the most capable and comprehensive tools for supporting server adapter teaming.

Features	Description
<b>General</b>	
RJ45 connections over CAT5e, CAT6, CAT6A cabling	<ul style="list-style-type: none"> <li>Ensures compatibility with cable lengths up to 100 meters. Two or four ports for maximum flexibility.</li> </ul>
Energy Efficient Ethernet (EEE)	<ul style="list-style-type: none"> <li>IEEE 802.3az enabled for reduced power consumption. Note: Enabled for 10/1GBASE-T, but not for 100BASE-TX</li> </ul>
Load balancing on multiple CPUs	<ul style="list-style-type: none"> <li>Increases performance on multi-processor systems by efficiently balancing network loads across CPU core when used with Receive-Side Scaling (RSS) from Microsoft or scalable I/O on Linux.</li> </ul>
Support for most network operating systems	<ul style="list-style-type: none"> <li>Enables broad deployment for different applications.</li> </ul>
Time Sync (IEEE 1588, 802.1as)	<ul style="list-style-type: none"> <li>Enables networked Ethernet equipment to synchronize internal clocks according to a network master clock; endpoint can then acquire an accurate estimate of the master time by compensating for link latency.</li> </ul>
<b>I/O Features for Multi-Core Processor Servers</b>	
Intel® Ethernet Flow Director (Intel® Ethernet FD)	<ul style="list-style-type: none"> <li>An advanced traffic steering capability increases the number of transactions per second and reduces latency for cloud applications like Memcached.</li> </ul>
MSI-X support	<ul style="list-style-type: none"> <li>Minimizes the overhead of interrupts.</li> <li>Load-balancing of interrupt handling between multiple cores/CPU's.</li> </ul>
Multiple Queues: 1,536 Tx and Rx queues per device	<ul style="list-style-type: none"> <li>Network packet handling without waiting for buffer overflow providing efficient packet prioritization.</li> <li>Actual number of queues will vary depending upon software implementation.</li> </ul>
Tx/Rx IP, SCTP, TCP, and UDP checksum offloading (IPv4, IPv6) capabilities	<ul style="list-style-type: none"> <li>Lower processor usage.</li> <li>Checksum and segmentation capability extended to new standard packet type.</li> </ul>
<b>Virtualization Features</b>	
VMDq	<ul style="list-style-type: none"> <li>Up to 256 maximum VMDq VMs supported.</li> <li>Offloads the data-sorting based on MAC addresses and VLAN tags, functionality from the Hypervisor to the network silicon, improving data throughput and CPU usage.</li> </ul>
PCI-SIG SR-IOV Implementation (128 per device)	<ul style="list-style-type: none"> <li>Integrated with Intel® VT for Directed I/O (Intel® VT-d) to provide data protection between VMs by assigning separate physical addresses in the memory to each VM.</li> <li>128 per device (64 per port for Dual Port adapter, 32 per port for Quad Port adapter).</li> </ul>
Virtual Machine Load Balancing (VLMB)	<ul style="list-style-type: none"> <li>VMLB provides traffic load balancing (Tx and Rx) across VMs bound to the team interface, as well as fault tolerance in the event of switch, port, cable, or adapter failure.</li> </ul>
Advanced Packet Filtering	<ul style="list-style-type: none"> <li>1536 exact matched packets (unicast or multicast).</li> <li>512 hash entries each for unicast and multicast.</li> <li>Lower processor usage.</li> <li>Promiscuous (unicast and multicast) transfer mode support.</li> <li>Optional filtering of invalid frames.</li> </ul>
VLAN support with VLAN tag insertion, stripping and packet filtering for up to 4096 VLAN tags	<ul style="list-style-type: none"> <li>Ability to create multiple VLAN segments.</li> </ul>
VXLAN, NVGRE, GENEVE, VXLAN-GPE+NSH, MPLS	<ul style="list-style-type: none"> <li>Preserves application performance in network virtualized environments.</li> </ul>
<b>Manageability Features</b>	
Preboot eXecution Environment (PXE) Support	<ul style="list-style-type: none"> <li>Enables system boot up via the LAN (32-bit and 64-bit).</li> <li>Flash interface for PXE image.</li> </ul>
Unified Extensible Firmware Interface (UEFI)	<ul style="list-style-type: none"> <li>Enables new technologies during the pre-OS boot process and addresses legacy BIOS limitations on hardware.</li> </ul>
Simple Network Management Protocol (SNMP) and Remote Network Monitoring (RMON) Statistic Counters	<ul style="list-style-type: none"> <li>Easy system monitoring with industry-standard consoles.</li> </ul>
iSCSI Boot	<ul style="list-style-type: none"> <li>Enables system boot up via iSCSI.</li> <li>Provides additional network management capability.</li> </ul>
Watchdog Timer	<ul style="list-style-type: none"> <li>Gives an indication to the manageability firmware or external devices that the controller or the software device driver is not functioning.</li> </ul>
Supported Management Implementations	<ul style="list-style-type: none"> <li>RBT</li> <li>MCTP</li> <li>RBT+MCTP</li> </ul>
NC-SI (DSP0222)	<ul style="list-style-type: none"> <li>Supports NC-SI 1.1 for Pass-Through and Control traffic.</li> </ul>
MCTP (DSP0236)	<ul style="list-style-type: none"> <li>Supports MCTP 1.2.</li> </ul>
MAC address provisioning	<ul style="list-style-type: none"> <li>Provisions one or more MAC addresses per NC-SI capable device that can be used for out of band management. (To be supported in an upcoming software update.)</li> </ul>
Temperature reporting (ASIC)	<ul style="list-style-type: none"> <li>Reports temperature of Intel® Ethernet Controller. (To be supported in an upcoming software update.)</li> </ul>
Estimated power consumption reporting	<ul style="list-style-type: none"> <li>Reports estimated power consumption of the adapter, excluding transceiver modules. (To be supported in an upcoming software update.)</li> </ul>
Firmware inventory and update	<ul style="list-style-type: none"> <li>Firmware inventory and update.</li> </ul>
Secure firmware	<ul style="list-style-type: none"> <li>Prevents the execution and update of unsigned and unauthenticated firmware components.</li> </ul>
NC-SI package addressing	<ul style="list-style-type: none"> <li>Assigns a unique ID to each Ethernet controller sharing a single NC-SI physical connection to prevent addressing conflicts.</li> </ul>

Specifications				
General				
Connections	RJ45 Copper			
RJ45 Copper	10GBASE-T: 55 m using CAT 6 , 100 m using CAT6A 100BASE-TX and 1000BASE-T: 100 m using CAT5e, CAT6, or CAT6A			
Thermals and Airflow				
	Heat sink to Port (0 - 65 °C) Minimum LFM	Heat sink to Port (0 - 55 °C) Minimum LFM	Port to heat sink (0 - 35 °C) Minimum LFM	
Dual Port	200 LFM	100 LFM	100 LFM	
Quad Port	330 LFM	200 LFM	100 LFM	
Technical Features				
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F )			
Storage Humidity	Maximum: 90% non-condensing relative humidity at 35 °C			
LED Indicators	LINK (green = 10Gbps; yellow = 5/2.5/1Gbps, 100Mbps) ACTIVITY (blinking green = transmitting or receiving data; off = no link)			
Intel Regulatory				
FCC Class A for World Wide EMC/EMI	Commercial usage			
Safety	UL 62368-1 and CAN/CSA C22.2 No. 62368-1-14 - Audio/video, information and communication technology equipment Part 1: Safety requirements  European Group Differences and National Differences according to EN 62368-1:2014			
RoHS-compliant	Product is compliant with EU RoHS Directive 2 2011/65/EU (Directive 2011/65/EU) and its amendments (e.g. 2015/863/EU)			
Adapter Features				
Data Rate Supported Per Port	10/1Gbps and 100Mbps			
Bus Type	PCI Express v3.0 (8 GT/s)			
Bus Width	PCI Express x8			
Interrupt Levels	INTA, MSI, MSI-X			
Hardware Certifications	FCC A, cUL <sub>US</sub> , CE, VCCI, BSMI, RCM, KCC, EEE			
Controller	Intel® Ethernet Controller X710-AT2 (Dual Port) Intel® Ethernet Controller X710-TM4 (Quad Port)			

Power Consumption				
	Dual Port		Quad Port	
Link Speed/Traffic	Typical Power	Max Power	Typical Power	Max Power
100 Mbps	4.9 W	5.3 W	6.2 W	6.8 W
1GbE	5.6 W	6.1 W	7.2 W	7.6 W
2.5GbE	6.5 W	6.6 W	10.2 W	11.4 W
5GbE	7.0 W	7.1 W	11.2 W	12.5 W
10GbE	8.8 W	9.5 W	13.4 W	14.2 W
Physical Dimensions				
Dimensions	115 mm x 76 mm (OCP NIC 3.0 Small Form Factor)			
Product Order Codes for PowerEdge				
Description	SKU	Dell Tech	Intel MM#	
X710T2LOCPV3	Factory installed: 540-BCRS Customer kit: 540-BCSG	VMFKR	999APZ	
X710T2LOCPV3 w/MCTP support	Factory installed: TBD Customer kit: TBD	F6X1R	99AL8T	
X710T4LOCPV3	Factory installed: 540-BCRU Customer kit: 540-BCSI	50RV4	999APX	
X710T4LOCPV3 w/MCTP support	Factory installed: TBD Customer kit: TBD	XC0M4	99C480	
Dell Tech Backing Information				
Standard one-year warranty.				

To see the full line of Intel Ethernet Network Adapters visit [www.dell.com](http://www.dell.com) or contact your Dell Technologies sales representative.

The information contained in this document, including all instructions, cautions, and regulatory approvals and certifications, is provided by Intel and has not been independently verified or tested by Dell. Dell cannot be responsible for damage caused as a result of either following or failing to follow these instructions. All statements or claims regarding the properties, capabilities, speeds or qualifications of the part referenced in this document are made by Intel and not by Dell. Dell specifically disclaims knowledge of the accuracy, completeness or substantiation for any such statements. All questions or comments relating to such statements or claims should be directed to Intel. Visit [www.dell.com](http://www.dell.com) for more information.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL

PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY INTEL, THE INTEL PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE INTEL PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information. The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request. Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order. Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or by visiting Intel's Web Site at <http://www.intel.com>.

© Intel Corporation. Intel, the Intel logo, and other Intel marks are trademarks of Intel Corporation or its subsidiaries. Other names and brands may be claimed as the property of others.