Noctua NH-U14S DX-4189 U-Type Premium Cooler



LOGISTIC DATA

| Product name |
|-------------------------------------|
| Noctua NH-U14S DX-4189 |
| EAN |
| 9010018000290 |
| UPC |
| 841501100291 |
| Packaging dimensions (HxWxD) |
| 159x227x204 mm |
| Weight incl. packaging |
| 1554 g |
| Warranty |
| 6 years |
| Packaging unit |
| 8 pcs |
| Packaging dimensions / unit (HxWxD) |
| 344x475x432 mm |
| Weight incl. packaging / unit |
| 13.60 kg |
| |

SCOPE OF DELIVERY

NH-U14S DX-4189 heatsink NF-A15 HS-PWM premium fan CPU carrier frame for LGA4189-4 (P4) NM-SMT5 Torx® T30 mounting tool SecuFirm2[™] mounting kit Anti-vibration pads and fan-dips for second NF-A15 NT-H1 thermal compound (pre-applied to the heatsink)

Noctua's DX line CPU coolers have become a default choice in premium grade quiet cooling solutions for Intel Xeon processors. The NH-U14S DX-4189 features a larger, custom-designed contact surface for LGA4189 platforms. Based on the proven, 140mm size NH-U14S heatsink and equipped with Noctua's award-winning, PWM controlled NF-A15 140mm fan, it combines maximum performance and superb acoustics. Topped off with the professional SecuFirm2™ mounting system and pre-applied NT-H1 thermal compound, the NH-U14S DX-4189 forms a complete premium quality package for quietly cooling LGA4189 based Xeon workstations and servers.

DX series for Intel Xeon

First introduced in 2008, Noctua's DX line CPU coolers have become a standard choice when it comes to quiet, premium grade air cooling solutions for Intel Xeon processors. Thanks to their superior acoustic efficiency, they are ideal for workstations and servers that run in noise sensitive environments (e.g. audio/video production, content creation, engineering, etc.).

Customised for I GA4189

The new DX-4189 line coolers are dedicated, customised solutions for Intel's professional LGA4189 platform (Whitley), which makes them an ideal fit for both Ice Lake-SP based 3rd generation Xeon Scalable CPUs (Platinum, Gold, Silver or Bronze) and W-3300 series Xeon processors for workstations (Ice Lake-64L).

LGA4189-4 (P4) CPU carrier frame


The scope of delivery includes an LGA4189-4 (P4) type CPU carrier frame for Intel Ice Lake-SP and Ice Lake-64L based processors (Whitley platform). However, the heatsink's SecuFirm2[™] mounting system also supports P5 type LGA4189 sockets (LGA4189-5) for Intel Cooper Lake based processors. CPU carrier frames for LGA4189-5 are available on request via support@noctua.at.

6-year manufacturer's warranty

Noctua products are renowned for their impeccable quality and outstanding longevity. True to this legacy, the NH-U14S DX-4189 heatsink is built to last, and like all Noctua fans, the supplied NF-A15 unit features an MTTF rating of more than 150,000 hours. The entire package comes with a full 6-year manufacturer's warranty.

NH-U14S DX-4189 HEATSINK SPECIFICATIONS

| Socket compatibility | Intel Xeon LGA4189 |
|-------------------------------------|--|
| Dimensions | 165x150x52 mm |
| Dimensions with NF-A15 HS-PWM | 165x150x78 mm |
| Weight | 797 g |
| Weight with NF-A15 HS-PWM | 957 g |
| Material | Copper (base and heatpipes), aluminium |
| | (cooling fins), soldered joints & nickel plating |
| Fan compatibility with 120 mm holes | 140x150x25 mm, 140x140x25 mm & |
| | 120x120x25 mm |
| | |



NF-A15 HS-PWM FAN SPECIFICATIONS

| Dimensions | 140x150x25 mm |
|--------------------------------|--|
| Connector | 4-pin PWM |
| Bearing | SS02 |
| Blade geometry | A-Series with Flow Acceleration Channels |
| Frame technology | AAO |
| Max. input power | 1.56 W |
| Voltage | 12 V |
| MTTF | > 150,000 h |
| Max. rotational speed (+/–10%) | 1500 RPM |
| Max. airflow | 140.2 m³/h |
| Max. acoustical noise | 24.6 dB(A) |
| Max. static pressure | 2.08 mm H ₂ 0 |

