RS501A-E12-RS4 AMD Turin 9005

AMD Single-socket, 1U Rack Server



Form Factor 1U | CPU Number 1 | Memory Number 24

5th Generation AMD EPYC Processors

ASUS RS501A-E12-RS4 was designed for general purpose application. With the front 4 hot-swap bays supporting 3.5” and 2.5” drives , RS501A-E12-RS4 is the economic design for rack placement.

FEATURE

- 1 x AMD EPYC 9005 Series Processor
- With 24*DDR5 DIMM up to 5200Mhz
- 2 x M.2 socket support
- 3 x PCIe + 1 x OCP expansion in 1U rack sever.

Target market

- General-purpose Rack Server
- Enterprise Application

AMD EPYC™ 9005 series processors support

RS501A-E12 series is built on the AMD platform to deliver incredible performance, and offer more CPU cores powered by AMD EPYC 9005 series processors.

Industry-leading memory capability

With 2 DIMM per channel design, RS501A-E12 Series supports up to 24 x DIMM slots. The CPU’s memory controller supports DDR5 memory with 12 channels up to 5200Mhz . We deliver the industry-leading technology of server memory for our customers’ business.

Comprehensive IT infrastructure management solution

ASUS RS501A-E12 features an embedded ASMB11-iKVM (BMC, AST2600) and is bundled with ASUS Control Center to provide comprehensive out-of-band and in-band management capability.



1. 4 x 3.5” / 2.5” Hot-swap Storage Bays
2. 1+1 Platinum/ Titanium CRPS CRPS
3. 1 x PCIe Gen5 x16 slot for full-height, half-length card
4. 1 x PCIe Gen5 x16 slot for low-profile card
5. 1 x PCIe Gen5 x16 slot for low-profile card
6. 1 x OCP 3.0 Mezzanine socket
7. AMD EPYC™ 9005 Processor Family (Up to 360W)
8. 24*DDR5 DIMM up to 5200Mhz

The specifications and price are subject to change without prior notice 2018 ASUSTek Computer Inc. All rights reserved.

RS501A-E12-RS4

SPECIFICATION

Processor		1 x Socket SP5 (LGA 6096) Supports AMD EPYC™ 9005 series processors or AMD EPYC™ 9004 series processors, up to 360W*
Memory	**Total Slots**	**24,** 12-channel, 2 DIMM per channel
	Capacity	Up to 3,072GB
	Memory Type	AMD EPYC™ 9005 series processors DDR5 6400/5600 RDIMM/3DS RDIMM 2DPC (1 of 2) up to 5200 with "6400 RDIMM", other 4800 2DPC (2 of 2, 1R+1R) up to 4400, with "6400 RDIMM", other 4000 2DPC (2 of 2, 2R+2R) up to 4000, with "6400 RDIMM", other 3600 AMD EPYC™ 9004 series processors DDR5 4800 RDIMM/ 3DS RDIMM 2DPC (1 of 2) up to 4800, 2DPC (2 of 2, 1R+1R) up to 4000 2DPC (2 of 2, 2R+2R) up to 3600
	Memory Size	128GB, 96GB, 64GB, 32GB, 16GB (RDIMM), *Refer to ASUS server AVL for the latest update
Expansion Slots	**Total Slots**	3 PCIe Gen5 slots + 1 OCP3.0
	Slot Type	1 x PCIe x16 slot (Gen5 x16 link, FH, HL) 1 x PCIe x16 slot (Gen5 x16 link, LP, HL) 1 x PCIe x16 slot (Gen5 x8 link, LP, HL) 1 x OCP3.0 socket (Gen5 x16 link)
Storage Bays		Front: 4 x 3.5"/2.5" Hot-swap Storage Bays (4 x SATA/SAS Devices) 2 x M.2 socket (Gen4 x4 link or SATA mode, up to 22110 module)
Networking	**LAN**	1 x Dual Port Intel I350-AM2 Gigabit LAN controller 1 x Dedicated management port (BMC, AST2600)
Security		Optional TPM module PFR module (support by project)
Rear I/O Ports		2 x USB 3.2 Gen1 ports 2 x Gigabit LAN ports (RJ45) 1 x Management port (RJ45) 1 x VGA port
Switch/LED		Front: 1 x Power Button/LED 1 x Location Button/LED 1 x Message LED 1 x HDD LED 4 x LAN LED (1-2 for on-board LAN, 3-4 for OCP LAN) Rear: 1 x Port80 LED (Q-Code) 1 x Power Switch w/ LED 1 x Location Switch w/ LED 1 x Message LED
OS Support		Please find the latest OS support from OS Compatibility Guide | ASUS
Management Solution	**Software**	ASUS Control Center (in-band)
	Out of Band Remote Management	ASMB11-iKVM (BMC, AST2600)
Dimension		842.5mm x 449mm x 43.85mm (1U) 33.17" x 17.68" x 1.73"
Net Weight Kg (CPU, DRAM & HDD not included)		13.15 kg
Gross Weight Kg (CPU, DRAM & HDD not included, Packing include)		18.15 kg
Power Supply (following different configuration by region)		1+1 Redundant 1200W Platinum Power Supply 1+1 Redundant 1600W Titanium Power Supply
Environment		Operation temperature: 10°C ~ 35°C Non operation temperature: -40°C ~ 70°C Non operation humidity: 20% ~ 90% (Non condensing)

*CPU with TDP supported under specific conditions. For higher wattage CPU demand, please contact us

The specifications and price are subject to change without prior notice 2018 ASUSTek Computer Inc. All rights reserved.

RS501A-E12 Series

SPECIFICATION

Series	RS501A-E12 Series Support Matrix		
Model	**RS501A-E12-RS12U**	**RS501A-E12-RS4**	**RS501A-E12-RS4U**
Processor	1 x Turin CPU or 1 x Genoa CPU		
GPU	Up to 2 single-slot GPU cards		
Memory	24 x DIMM slots with AMD EPYC™ 9005 series processors DDR5 6400/5600 RDIMM/3DS RDIMM Maximum 3,072GB 2DPC (1 of 2) up to 5200 with "6400 RDIMM", other 4800 2DPC (2 of 2, 1R+1R) up to 4400, with "6400 RDIMM", other 4000 2DPC (2 of 2, 2R+2R) up to 4000, with "6400 RDIMM", other 3600 with AMD EPYC™ 9004 series processors DDR5 4800 RDIMM/ 3DS RDIMM Maximum 3,072GB 2DPC (1 of 2) up to 4800, 2DPC (2 of 2, 1R+1R) up to 4000 2DPC (2 of 2, 2R+2R) up to 3600		
M.2	2 x PCIe x4 or 2 x SATA		
Expansion	1 x PCIe x16 slot (Gen5 x16 link, FH, HL) 1 x PCIe x16 slot (Gen5 x16 link, LP, HL) 1 x PCIe x16 slot (Gen5 x8 link, LP, HL) 1 x OCP3.0 socket (Gen5 x16 link)		
Storage	**w mid-bay** Front bays: 12 x 2.5" Hot-Swap drive bays 12 x SATA/SAS/NVMe Mid-bay: 4 x 2.5" storage bays support NVMe /SATA *SAS support only from optional SAS HBA/RAID card **Internal Storage Bays is designated as build-to-order only, owing to quality or installation concerns. **w/o mid-bay** Front bays: 12 x 2.5" Hot-Swap drive bays 12 x SATA/SAS/NVMe *SAS support only from optional SAS HBA/RAID card	Front bays: 4 x 3.5"/2.5" Hot-Swap drive bays Support up to 4 x SATA/SAS/NVMe* *SAS support only from optional SAS HBA/RAID card *MCIO cable is required to support NVMe hard drives	Front bays: 4 x 2.5" Hot-Swap drive bays Support up to 4 x SATA/SAS /NVMe* *SAS support only from optional SAS HBA/RAID card
NIC	2 x 1GbE RJ45 onboard LAN ports (Intel i350-AM2 controller) 2 x 10Gb OCP Card (Optional) 1 x Management LAN		

* The total number of NVMe drives installed will affect the total number of GPUs that can be installed.

The specifications and price are subject to change without prior notice 2018 ASUSTek Computer Inc. All rights reserved.