

# XV24-SU0-AAJ1

NVIDIA MGX™ Server - 2U UP 4 x PCIe Gen5 GPUs



## Key Features

- Supports up to 4 x Dual slot Gen5 GPUs
- Supports 4 x NVIDIA H200 NVL PCIe GPUs with 2-way NVLink bridges or 4 x NVIDIA RTX PRO™ 6000 Blackwell Server Edition GPUs
- NVIDIA MGX™ modular server design
- Single Intel® Xeon® 6700/6500-Series Processors with 136 PCIe lanes
- 8-Channel DDR5 RDIMM / MRDIMM, 16 x DIMMs
- Dual ROM Architecture
- 2 x 10Gb/s LAN ports via Intel® X550-AT2
- 2 x 2.5" Gen5 NVMe hot-swap bays
- 2 x M.2 slots with PCIe Gen5 x4 interface
- 4 x FHFL PCIe Gen5 x16 slots for GPUs
- 2 x FHFL PCIe Gen5 x16 slots for NVIDIA ConnectX®-7 NICs
- 1 x FHFL PCIe Gen5 x16 slot for NVIDIA® BlueField®-3 DPUs
- 3+1 2000W 80 PLUS Titanium redundant power supplies



## Specification

Dimensions	2U (W438 x H87 x D900 mm)	PCIe Expansion Slots	4 x FHFL PCIe Gen5 x16, for GPUs 2 x FHFL PCIe Gen5 x16, for NICs 1 x FHFL PCIe Gen5 x16, for DPUs
Motherboard	MSU4-MG0	I/O Ports	<b>Front:</b> 2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6700-Series Processors with 136 PCIe lanes - Intel® Xeon® 6500-Series Processors with 136 PCIe lanes Single processor, TDP up to 350W	Backplane Board	PCIe Gen5 x4
OS Compatibility	<a href="#">OS Support List</a>	TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM012 1 x PRoT connector (only enabled on RoT SKU)
Socket	1 x LGA 4710 (Socket E2)	Power Supply	3+1 2000W 80 PLUS Titanium redundant power supplies AC Input: 100-240V
Chipset	System on Chip	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Memory	8-Channel DDR5 RDIMM/MRDIMM, 16 x DIMMs [RDIMM] Up to 6400 MT/s (1DPC), 5200 MT/s (2DPC) [MRDIMM] Up to 8000 MT/s <sup>[1]</sup>  <sup>[1]</sup> MRDIMMs are only supported in a 1DPC configuration.	System Fans	2 x 60x60x56mm 4 x 80x80x80mm
LAN	2 x 10Gb/s LAN (1 x Intel® X550-AT2), Support NCSI 1 x 10/100/1000 Mbps Management LAN	Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Packaging Content	1 x XV24-SU0-AAJ1 2 x CPU heatsinks 1 x Mini-DP to D-Sub cable 2 x GPU power cables (16-pin, 450mm) 2 x GPU power cables (16-pin, 550mm) 1 x DPU power cable (2x PCIe 8pin, 520mm) 2 x Carriers 1 x 3-Section Rail kit
Storage	<b>Front hot-swap:</b> 2 x 2.5" Gen5 NVMe <b>Internal M.2:</b> 2 x M.2 (2242/2260/2280/22110), PCIe Gen5 x4	Ordering Part Numbers	6NXV24SU0DR000AAJ1*
RAID	Onboard VROC key header	Optional Parts	- Chassis intrusion switch: 25HA1-R28390-U1R - Cable Management Arm: 25HB2-2AA700-K0R



Learn more at: <https://www.gigabyte.com/Enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

