

## KIOXIA PM6-R Series (2.5-inch) (KPM61RUG/KPM6XRUG/KPM6VRUG/KPM6WRUG) Enterprise SAS Read Intensive SSD

KIOXIA PM6-R Series 24G SAS Enterprise SSD is optimized for read intensive applications, including web services, data warehousing, streaming media and video on demand. The series provides high levels of performance, reliability and endurance, and is designed to minimize total cost of ownership.

Featuring KIOXIA Corporation's 96-layer BiCS FLASH™ 3D flash memory, this 6th generation enterprise SAS SSD PM6-R Series offers 1 DWPD (Drive Writes Per Day) with capacities up to 30.72 TB.



Product image may represent a design model.

### Key Features

- 24G SAS interface with single/dual-port support
- Capacities from 960 GB to 30.72 TB
- Up to 595K random read IOPS (4 KiB) in dual-port mode
- 2.5-inch form factor, 15 mm thickness
- 1 DWPD with 100 % Random Write Workload
- Power Loss Protection and End-to-End Data Protection, including T10 DIF
- Security options: SIE, SED, FIPS SED<sup>[1][2][3][4][5]</sup>
- 5-year limited warranty

### Key Applications

- Data warehousing
- Streaming media
- Video on demand (VOD)
- Web servers

### Specifications

Base Model Number	KPM61RUG30T7	KPM61RUG15T3	KPM61RUG7T68	KPM61RUG3T84	KPM61RUG1T92	KPM61RUG960G
SIE Model Number	KPM6XRUG30T7	KPM6XRUG15T3	KPM6XRUG7T68	KPM6XRUG3T84	KPM6XRUG1T92	KPM6XRUG960G
SED Model Number	KPM6VRUG30T7	KPM6VRUG15T3	KPM6VRUG7T68	KPM6VRUG3T84	KPM6VRUG1T92	KPM6VRUG960G
FIPS SED Model Number	KPM6WRUG30T7	KPM6WRUG15T3	KPM6WRUG7T68	KPM6WRUG3T84	KPM6WRUG1T92	KPM6WRUG960G
Capacity	30,720 GB	15,360 GB	7,680 GB	3,840 GB	1,920 GB	960 GB
<b>Basic Specifications</b>						
Form Factor	2.5-inch, 15 mm thickness					
Interface	SAS-4					
Interface Speed	22.5 Gbit/s, 12.0 Gbit/s, 6.0 Gbit/s, 3.0 Gbit/s, 1.5 Gbit/s					
Flash Memory Type	BiCS FLASH™ TLC					

## Specifications (Continued)

Capacity	30,720 GB	15,360 GB	7,680 GB	3,840 GB	1,920 GB	960 GB
<b>Performance (Up to)</b>						
Sustained 128 KiB Sequential Read	4,150 MB/s					
Sustained 128 KiB Sequential Write	3,200 MB/s	3,700 MB/s		2,450 MB/s	2,700 MB/s	1,450 MB/s
Sustained 4 KiB Random Read	595K IOPS					
Sustained 4 KiB Random Write	80K IOPS	160K IOPS	155K IOPS	115K IOPS	125K IOPS	75K IOPS
<b>Power Requirements</b>						
Supply Voltage	12 V ± 10 %, 5 V +10 % / -7 %					
Power Consumption (Ready)	5 W typ.					
<b>Reliability</b>						
MTTF	2,500,000 hours					
Warranty	5 years					
DWPD	1					
<b>Dimensions</b>						
Thickness	15.0 mm +0 / -0.5 mm					
Width	69.85 mm ± 0.25 mm					
Length	100.45 mm Max					
Weight	150 g Max	130 g Max				
<b>Environmental</b>						
Temperature (Operating)	0 °C to 70 °C					
Temperature (Non-operating)	-40 °C to 80 °C					
Humidity (Operating)	5 % to 95 % R.H.					
Vibration (Operating)	21.27 m/s <sup>2</sup> { 2.17 Grms } ( 5 to 800 Hz )					
Shock (Operating)	9.8 km/s <sup>2</sup> { 1,000 G } ( 0.5 ms )					

Definition of capacity: KIOXIA Corporation defines a megabyte (MB) as 1,000,000 bytes, a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1 GB = 2<sup>30</sup> = 1,073,741,824 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

GT/s: Giga Transfers per second.

A kibibyte (KiB) means 2<sup>10</sup>, or 1,024 bytes.

MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

DWPD: Drive Writes Per Day. One full drive write per day means the drive can be written and re-written to full capacity once a day every day for the specified lifetime. Actual results may vary due to system configuration, usage and other factors.

Read and write speed may vary depending on various factors such as host devices, software (drivers, OS etc.), and read/write conditions.

IOPS: Input Output Per Second (or the number of I/O operations per second).

[1] Sanitize Instant Erase (SIE), Self-Encrypting Drive (SED) and FIPS (Federal Information Processing Standards) SED security optional models are available.

[2] SIE optional model supports Crypto Erase, which is a standardized feature defined by the technical committees (T10) of INCITS (the InterNational Committee for Information Technology Standards).

[3] SED optional model supports TCG Enterprise SSC.

[4] FIPS SED optional model utilizes a security module designed to comply with FIPS 140-2 and FIPS 140-3, which define security requirements for cryptographic module by NIST (National Institute of Standards and Technology). For the latest validation status, please make inquiries through "Contact us" in each region's website, <https://www.kioxia.com/>.

[5] Security optional models are not available in all countries due to export and local regulations.

Other company names, product names, and service names may be trademarks of third-party companies.